



Choose the safest and most productive Hilti tool

Contents	Page
How to read the Tool Selector	2
Rotary Hammers - hammer drilling	3 - 4
Combihammers - hammer drilling concrete	5 - 7
Combihammers / Breakers/Rotaries - chiseling demolition	8
Drill drivers / Rotary Hammers - drilling steel	9 - 12
Drill drivers / Universal Hammers/Rotaries - drilling concrete	13
Impact Fastening	14
Diamond coring & grinding tools	15 - 17
Diamond cutting tools	18 - 19
Angle grinders	20
Steel cutting tools	21 - 32
Direct Fastening tools	33 - 34
Saws	35 - 37
Hydraulic pressure / cutting tools	38
Disclaimer	39

How to read the Tool Selector

Sound pressure value

The sound pressure level is the physical value which is directly processed by the human ear. It is measured with standard microphones in accordance with EN 60745-2-X or EN62841-2-X. The sound pressure level is strongly dependent on the location of the tool in relation to the microphone. Due to this dependence it is not a reliable quantity for technical documentation. Therefore, we also declare sound power value. Both values are measured in accordance with the relevant standards EN 60745-2-X or EN62841-2-X, while taking into account the measurement instructions for specific tool classes within the standards.

Sound power value

This value is computed from several sound pressure levels at different measurement locations. It stands for an overall acoustic energy dissipated by the tool. While using a tool, protective equipment should be used as specified by the manufacturer in the relevant documents.

Vibration values

Measured in accordance with EN 60745. In certain applications where EN 60745 may not apply, BS EN 5349 is used. All data complies with the Control of Vibration at Work Regulations 2005. The tri-axial vibration value is required for risk analysis.

EAV

The "Exposure Action Value" (EAV) of 2.5 m/s² is the safer limit and can be worked to without any additional controls in place (risk assessment, health surveillance, inspection etc.). Employees should always aim to work to the EAV.

ELV

The "Exposure Limit Value" (EAV) of 5 m/s² is the absolute maximum weighted average level for an 8 hour working shift. If an average exposure of 2,5m/s² within an 8 hour working shift is exceeded, the employer has to take action in accordance with the local legislation.

Consumables

All values given are valid only for the given tool and consumable as well as the base material.

HSE Points

The exposure points system is a simple alternative for describing and managing exposures in the workplace. It helps to make the system more tangible and is useful especially when carrying out more than one applications per day.

In this product selector the **HSE points** system have been combined with Hilti's productivity figures.

The EAV allows a maximum of 100 point per day.

The ELV allows a maximum of 400 point per day.

Example:

Tool	Material	Detail	HSE Points	Applications	Total Points
TE 2	Concrete 40 N/mm ²	Hole depth: 100 mm Hole diameter: 10 mm	2,0	20	40
TE 76-ATC	Concrete 40 N/mm ²	Hole depth: 100 mm Hole diameter: 24 mm	2,7	10	27
DX 76	-	Cartridge: Red	0,1667	50	8,3
GX 120	-	-	0,0286	100	2,9
					78,2

This case comes in at below the EAV.

Applications

Drilling

The number of holes that can be drilled for a particular tool and given diameter, depth, work piece material and consumable in a working day before the EAV and ELV (shown in brackets) are given under the productivity data section. The red value is the number of HSE points per hole for the given tool and application.

Breaking

The volume of material that can be broken for a particular tool and given work piece material and consumable in a working day before the EAV and ELV (shown in brackets) are given in the productivity data section. The red value is the number of HSE points per litre for the given tool and application.

Impact Fastening

The number of nails that can be set for a particular tool and given work piece material and nail type in a working day before the EAV and ELV (shown in brackets) are given under the productivity data section. The red value is the number of HSE points per hole for the given tool and application.

Diamond Coring

The number of holes that can be made for a particular tool given diameter, depth, work piece material and consumable in one working day before reaching the EAV and ELV (shown in brackets) are given under the productivity data. The red value is the number of HSE points per hole for the given application (hand held).

Fastening

The cartridge colour is listed followed by the number of fastenings that can be made in a given day before reaching the EAV and ELV. The HSE points per fixing are listed.

Cutting

The length of material and number of cuts that can be made for a particular tool and application in one working day before reaching the EAV and ELV are listed under the productivity data.

Rotary hammers cordless

Basic tool data								Productivity data									
Tool	Dust removal available	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for drilling diameter (mm)							
										HSE points per hole							
										6	8	10	12	14	16	18	20
TE 2-A (01)	DRS-S	86 dB(A)	97 dB(A)	14.5 m/s ²	1.5 m/s ²	14 min.	57 min.	concrete 40 N/mm ²	TE-CX	129	119	47	36				
										(516)	(476)	(188)	(144)				
										0,80	0,84	2,13	2,78				
TE 2-A22 (02)	DRS-S	92 dB(A)	103 dB(A)	15.0 m/s ²	1.5 m/s ²	13 min.	52 min.	concrete 40 N/mm ²	TE-CX	132	117	88	66	55	46		
										(528)	(468)	(352)	(264)	(220)	(184)		
										0,76	0,85	1,14	1,52	1,82	2,17		
TE 4-A22 (01)	no	88 dB(A)	99 dB(A)	11 m/s ²	1.5 m/s ²	25 min.	100 min.	concrete 40 N/mm ²	TE-C3X	256	246	219	180	131	66		
										(1024)	(984)	(472)	(500)	(352)	(268)		
										0,39	0,41	0,46	0,55	0,77	1,51		
TE 4-A22 (02)	DRS-4-A	88 dB(A)	99 dB(A)	11 m/s ²	1.5 m/s ²	25 min.	100 min.	concrete 50/60 N/mm ²	TE-CX	301	259	210	168	133	99		
										(1204)	(1036)	(840)	(672)	(532)	(396)		
										0,33	0,39	0,48	0,60	0,76	1,02		
TE 6-A (01)	DRS-S	90 dB(A)	101 dB(A)	11 m/s ²	1.5 m/s ²	25 min.	99 min.	concrete 40 N/mm ²	TE-CX	251	219	94	75	61	45		
										(1004)	(876)	(376)	(300)	(244)	(180)		
										0,40	0,46	1,06	1,33	1,64	2,22		
TE 6-A22 (04)	DRS-6A	89 dB(A)	100 dB(A)	13.4 m/s ²	1.5 m/s ²	17 min.	67 min.	concrete 50/60 N/mm ²	TE-C	277	230	190	141	128	101		
										(1108)	(920)	(760)	(564)	(512)	(404)		
										0,37	0,44	0,54	0,72	0,79	1,01		
TE 6-A36-AVR (03)	DRS-TE6-A	88 dB(A)	99 dB(A)	9 m/s ²	1.5 m/s ²	37 min.	148 min.	concrete 40 N/mm ²	TE-C3X	318	366	162	185	139	90		
										(1272)	(1464)	(648)	(740)	(556)	(360)		
										0,31	0,27	0,62	0,54	0,72	1,11		
TE 6-A36-AVR (04)	DRS-TE6-A	91 dB(A)	102 dB(A)	13 m/s ²	1.5 m/s ²	18 min.	71 min.	concrete 50/60 N/mm ²	TE-CX	289	240	199	148	134	106	93	87
										(1156)	(960)	(796)	(592)	(536)	(424)	(372)	(348)
										0,35	0,42	0,50	0,68	0,75	0,94	1,08	1,15
TE 7-A (01)	DRS-M	88 dB(A)	99 dB(A)	11 m/s ²	1.5 m/s ²	25 min.	99 min.	concrete 40 N/mm ²	TE-CX	228	237	126	112	85	69		35
										(912)	(948)	(504)	(448)	(340)	(276)		(140)
										0,44	0,42	0,79	0,89	1,18	1,45		2,86

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Drilling

The number of holes that can be drilled for a particular tool and given diameter, depth, work piece material and consumable in a working day before the EAV and ELV (shown in brackets) are given in the productivity data section. The red value is the number of HSE points per hole for the given tool and application.

Rotary hammers

Basic tool data								Productivity data													
Tool	Dust removal available	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for drilling diameter (mm) HSE points per hole											
										Hole depth 50mm				Hole depth 100mm							
										6	8	10	12	14	16	18	20	25	28		
TE 1 (02)	DRS-S	89 dB (A)	100 dB (A)	15 m/s ²	1.5 m/s ²	13 min.	52 min.	concrete 40 N/mm ²	TE-CX		133	56	41								
											(532)	(224)	(164)								
											0,75	1,79	2,44								
TE 2 (all types) (01)	DRS-S	89 dB (A)	100 dB (A)	16 m/s ²	1.5 m/s ²	12 min.	47 min.	concrete 40 N/mm ²	TE-CX		116	49	39								
											(464)	(196)	(156)								
											0,86	2,04	2,56								
TE 2 (02) all types	DRS-S	91 dB (A)	102 dB (A)	13.5 m/s ²	1.5 m/s ²	16 min.	66 min.	concrete 40 N/mm ²	TE-CX		171	163	73	61							
											(684)	(662)	(292)	(244)							
											0,58	0,61	1,37	1,64							
TE 6-S (01)	DRS-M	87 dB (A)	98 dB (A)	11 m/s ²	1.5 m/s ²	25 min.	99 min.	concrete 40 N/mm ²	TE-CX		247	111	79	73	56						
											(988)	(444)	(316)	(292)	(224)						
											0,40	0,90	1,27	1,37	1,79						
TE 7 (02)	DRS-M	89 dB (A)	100 dB (A)	11 m/s ²	1.5 m/s ²	25 min.	100 min.	concrete 40 N/mm ²	TE-C3X			84									
												(336)									
												1,19									
TE 7-C (01)	DRS-S	89 dB (A)	100 dB (A)	17 m/s ²	1.5 m/s ²	10 min.	42 min.	concrete 40 N/mm ²	TE-CX		103	107	52	45	34	28	18	14			
											(412)	(428)	(208)	(180)	(136)	(112)	(72)	(56)			
											0,97	0,93	1,92	2,22	2,94	3,57	5,56	7,14			
TE 16 (all types) (01)	DRS-S	89 dB (A)	100 dB (A)	16.5 m/s ²	1.5 m/s ²	11 min.	44 min.	concrete 40 N/mm ²	TE-CX		123	63	60		40		19				
											(492)	(252)	(240)		(160)		(76)				
											0,81	1,59	1,67		2,50		5,26				

* Emission sound pressure level L_{pA} and triaxial vibration value a_{hv} according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (K): noise 3dB.

Drilling

The number of holes that can be drilled for a particular tool and given diameter, depth, work piece material and consumable in a working day before the EAV and ELV (shown in brackets) are given in the productivity data section. The red value is the number of HSE points per hole for the given tool and application.

Combihammers - hammer drilling in concrete

Basic tool data								Productivity data																					
Tool	Dust removal available	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Workpiece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for drilling diameter (mm)																			
										HSE points per hole Hole depth 100mm																			
										8	10	12	14	16	18	20	22	24	25	26	28	30	32						
TE 3-C (01)	DRS-S	92 dB (A)	103 dB (A)	15.5 m/s ²	1.5 m/s ²	12 min.	50 min.	concrete 50/60 N/mm ²	TE-CX, TE-C3X	76	61	46	37	31															
										(318)	(255)	(190)	(156)	(129)															
										1,26	1,57	2,11	2,57	3,10															
TE 3-M (01)	DRS-S	91 dB (A)	102 dB (A)	15.5 m/s ²	1.5 m/s ²	12 min.	50 min.	concrete 50/60 N/mm ²	TE-CX, TE-C3X	76	61	46	37	31															
										(318)	(255)	(190)	(156)	(129)															
										1,26	1,57	2,11	2,57	3,10															
TE 30 (01)	DRS-S	90 dB (A)	101 dB (A)	16.5 m/s ²	1.5 m/s ²	11 min.	44 min.	concrete 40 N/mm ²	TE-CX, TE-C3X	60	61			41		19													
										(240)	(244)			(164)		(76)													
										1,67	1,64			2,44		5,26													
TE 30-ATC/AVR (02)	DRS-S	88 dB (A)	99 dB (A)	10 m/s ²	1.5 m/s ²	30 min.	120 min.	concrete 40 N/mm ²	TE-CX	280	210	180		140		80		62				30							
										(1120)	(840)	(720)		(560)		(320)		(248)		(120)									
										0,36	0,48	0,56		0,71		1,25		1,61		3,33									
TE 30-ATC/AVR (02)	DRS-S	88 dB (A)	99 dB (A)	10 m/s ²	1.5 m/s ²	30 min.	120 min.	concrete 50/60 N/mm ²	TE-CX	187	159			110		71													
										(749)	(637)			(442)		(283)													
										0,53	0,63			0,91		1,41													
TE 30-AVR (01)	DRS-S	90 dB (A)	101 dB (A)	12 m/s ²	1.5 m/s ²	21 min.	84 min.	concrete 40 N/mm ²	TE-CX, TE-C3X	114	116			78		36													
										(456)	(464)			(312)		(144)													
										0,90	0,80			1,20		2,70													
TE 30-AVR (02)	DRS-S	93 dB (A)	103 dB (A)	9.2 m/s ²	1.5 m/s ²	35 min.	140 min.	concrete 50/60 N/mm ²	TE-CX, TE-C3X	437	371			258		165													
										(1748)	(1484)			(1032)		(660)													
										0,23	0,27			0,38		0,60													
TE 30-C-AVR (01)	DRS-S	90 dB (A)	100 dB (A)	12 m/s ²	1.5 m/s ²	21 min.	84 min.	concrete 40 N/mm ²	TE-CX, TE-C3X	114	116			78		36													
										(456)	(464)			(312)		(144)													
										0,88	0,86			1,28		2,78													
TE 30-M-AVR (01)	DRS-S	90 dB (A)	101 dB (A)	12 m/s ²	1.5 m/s ²	21 min.	84 min.	concrete 40 N/mm ²	TE-CX, TE-C3X	114	116			78		36													
										(456)	(464)			(312)		(144)													
										0,88	0,86			1,28		2,78													
TE 40 (01)	DRS-S	93 dB (A)	104 dB (A)	16.3 m/s ²	1.5 m/s ²	11 min.	45 min.	concrete 40 N/mm ²	TE-CX	52				29		20													
										(208)				(116)		(80)													
										1,92				3,45		5,00													
TE 40-AVR (01)	DRS-S	94 dB (A)	105 dB (A)	10.7 m/s ²	1.5 m/s ²	26 min.	105 min.	concrete 40 N/mm ²	TE-CX	121				67		46													
										(484)				(268)		(184)													
										0,83				1,49		2,17													
TE 50 (02)	DRS-Y	95 dB (A)	106 dB (A)	16.1 m/s ²	1.5 m/s ²	12 min.	46 min.	concrete 40 N/mm ²	TE-YX	50				29		22	20				12								
										(200)				(116)		(88)	(80)		(48)										
										2,00				3,45		4,55	5,00		8,33										
TE 50-AVR (02)	DRS-Y	97 dB (A)	108 dB (A)	8 m/s ²	1.5 m/s ²	47 min.	188 min.	concrete 50/60 N/mm ²	TE-YX	327				254		182						105							
										(1308)				(1016)		(728)			(420)										
										0,31				0,39		0,55			0,95										
TE 50-AVR (03)	DRS-Y	97 dB (A)	108 dB (A)	8 m/s ²	1.5 m/s ²	47 min.	188 min.	concrete 50/60 N/mm ²	TE-YX	323	289	258	228	200	176	153	143				114	97	83						
										(1292)	(1156)	(1032)	(912)	(800)	(704)	(612)	(572)		(456)	(388)	(332)								
										0,31	0,35	0,39	0,44	0,50	0,57	0,65	0,70		0,88	1,03	1,20								
TE 56 (01)	DRS-Y	92 dB (A)	103 dB (A)	17 m/s ²	1.5 m/s ²	10 min.	42 min.	concrete 40 N/mm ²	TE-YX	47				29		22					17	13							
										(188)				(116)		(88)			(68)	(52)									
										2,13				3,45		4,55			5,88	7,69									

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (K): noise 3dB.

Combihammers - hammer drilling in concrete

Basic tool data								Productivity data													
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for drilling diameter (mm)											
										HSE points per hole											
										Hole depth 100mm											
										16	18	20	22	24	25	28	30	32	37	38	40
TE 56-ATC (01)	DRS-Y	92 dB (A)	103 dB (A)	16 m/s ²	1.5 m/s ²	12 min.	47 min.	concrete 40 N/mm ²	TE-YX			33 (132) 3,03		25 (100) 4,00		20 (80) 5,00	14 (56) 7,14				
TE 60-T-ATC (02)	DRS-Y	99 dB (A)	110 dB (A)	9 m/s ²	1.5 m/s ²	37 min.	148 min.	concrete 40 N/mm ²	TE-YX			113 (452) 0,88		82 (328) 1,22		56 (224) 1,79					
TE 60-AVR (04)	DRS-Y	96 dB (A)	107 dB (A)	9.6 m/s ²	1.5 m/s ²	33 min.	130 min.	concrete 50/60 N/mm ²	TE-YX			242 (968) 0,42		202 (808) 0,50		119 (476) 0,85				76 (304) 1,33	
TE 60-ATC (03)	DRS-Y	101 dB (A)	112 dB (A)	11 m/s ²	1.5 m/s ²	25 min.	100 min.	concrete 40 N/mm ²	TE-YX			76 (304) 1,32		69 (276) 1,45		42 (168) 2,38					
TE 60-ATC-AVR (03)	DRS-Y	101 dB (A)	112 dB (A)	7.5 m/s ²	1.5 m/s ²	53 min.	212 min.	concrete 40 N/mm ²	TE-YX			185 (740) 0,54		150 (600) 0,67		94 (376) 1,06					
TE 60-ATC-AVR (04)	DRS-Y	100 dB (A)	111 dB (A)	6.4 m/s ²	1.5 m/s ²	73 min.	293 min.	concrete 50/60 N/mm ²	TE-YX			534 (2136) 0,18		446 (1784) 0,22		263 (1052) 0,38				168 (672) 0,59	
TE 70 (02)	DRS-Y	99 dB (A)	110 dB (A)	22 m/s ²	1.5 m/s ²	6 min.	25 min.	concrete 40 N/mm ²	TE-YX			25 (100) 4,00		21 (84) 4,76	18 (72) 5,56		15 (60) 6,67		10 (40) 10,00	7 (28) 14,29	
TE 70-ATC (02)	DRS-Y	99.5 dB (A)	110.5 dB (A)	22 m/s ²	1.5 m/s ²	6 min.	25 min.	concrete 40 N/mm ²	TE-YX			25 (100) 4,00		21 (84) 4,76	18 (72) 5,56		15 (60) 6,67		10 (40) 10,00	7 (28) 14,29	
TE 70-AVR (03)	DRS-Y	102 dB (A)	113 dB (A)	10 m/s ²	1.5 m/s ²	30 min.	120 min.	concrete 40 N/mm ²	TE-YX	140	120	125	120		105	90		65	50		40
TE 70-D/AVR (03)										(560)	(480)	(500)	(480)		(420)	(360)		(260)	(200)		(160)
TE 70-ATC/AVR (03)										0,71	0,83	0,80	0,83		0,95	1,11		1,54	2,00		2,50

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Combihammers cordless - hammer drilling in concrete

Basic tool data								Productivity data													
Tool	Dust removal available	Emission sound pressure level LpA *	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for drilling diameter (mm)											
										HSE points per hole											
										Hole depth 100mm											
										10	12	14	16	18	20	22	24	25	28	30	32
TE 30-A 36 (02)	DRS-S	88 dB (A)	99 dB (A)	10.6 m/s ²	1.5 m/s ²	27 min.	107 min.	concrete 50/60 N/mm ²	TE-CX TE-CP TE-C-BK	309 (1236) 0,32	263 (1052) 0,38	221 (804) 0,45	183 (732) 0,55	148 (592) 0,68	117 (472) 0,86	92 (360) 1,12	66 (264) 1,52	55 (220) 1,81			
TE 30-A 36 (03)	DRS-Y	96 dB (A)	107 dB (A)	9.6 m/s ²	1.5 m/s ²	33 min.	130 min.	concrete 50/60 N/mm ²	TE-YX	333 (1332) 0,3	283 (1332) 0,35	238 (952) 0,42	197 (788) 0,51	159 (636) 0,63	126 (504) 0,8	97 (388) 1,03	72 (288) 1,4	60 (240) 1,66			
TE 60-A36 (04)	DRS-Y	101 dB (A)	112 dB (A)	11 m/s ²	1.5 m/s ²	25 min.	100 min.	concrete 40 N/mm ²	TE-YX	464 (1856) 0,22	418 (1672) 0,24	375 (1500) 0,27	335 (1340) 0,3	300 (1200) 0,33	264 (1056) 0,38	233 (932) 0,43	214 (856) 0,47	179 (716) 0,56	156 (624) 0,64	140 (560) 0,72	

Combihammers - hammer drilling in concrete

Basic tool data								Productivity data														
Tool	Dust removal available	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for drilling diameter (mm)												
										HSE points per hole												
										Hole depth 100mm												
										16	18	20	22	24	25	28	30	32	36	37	38	40
TE 76 (01)	DRS-Y	91 dB (A)	102 dB (A)	17 m/s ²	1.5 m/s ²	10 min.	42 min.	concrete 40 N/mm ²	TE-YX					29 (116)		21 (84)		17 (68)			13 (52)	
													3,45		4,76		5,88			7,69		
TE 76P-ATC (01)	DRS-Y	91 dB (A)	102 dB (A)	15 m/s ²	1.5 m/s ²	13 min.	53 min.	concrete 40 N/mm ²	TE-YX					37 (148)		26 (104)		22 (88)			16 (64)	
													2,70		3,85		4,55			6,25		
TE 80-ATC (01)	DRS-Y	99.5 dB (A)	110.5 dB (A)	8.8 m/s ²	1.5 m/s ²	39 min.	155 min.	concrete 40 N/mm ²	TE-YX				171 (684)		144 (576)	131 (524)	109 (436)	93 (372)	70 (280)			53 (212)
													0,58		0,69	0,76	0,92	1,08	1,43			1,89
TE 80-ATC /AVR (03)	DRS-Y	102 dB (A)	113 dB (A)	7.5 m/s ²	1.5 m/s ²	53 min.	212 min.	concrete 40 N/mm ²	TE-YX	250 (1000)	210 (840)	220 (880)	212 (848)		185 (740)	165 (660)		115 (460)		92 (368)		75 (300)
										0,40	0,48	0,45	0,47		0,54	0,61		0,87		1,09		1,33

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x. Uncertainty (k): noise 3dB.

Combihammers - chiseling to wall

Basic tool data								Productivity data				
Tool	Dust removal available	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Volume till EAV (liter)	Volume till ELV (liter)	HSE Points
TE 30-ATC/AVR (02)	DRS-S	88 dB (A)	99 dB (A)	9 m/s ²	1.5 m/s ²	37 min.	148 min.	concrete 40 N/mm	TE-CP-SM 25			
TE 30-C-AVR (01)	no	90 dB (A)	111 dB (A)	11 m/s ²	1.5 m/s ²	25 min.	100 min.	concrete 40 N/mm	TE-CP-SM 25	7	28	14,29
TE 30-M-AVR (01)	no	90 dB (A)	111 dB (A)	11 m/s ²	1.5 m/s ²	25 min.	100 min.	concrete 40 N/mm	TE-CP-SM 25	7	28	14,29
TE 56 / TE 56-ATC (01)	DRS-Y	92 dB (A)	103 dB (A)	13 m/s ²	1.5 m/s ²	18 min.	71 min.	concrete 40 N/mm	TE-YP-SM 28	14,9	59	6,71
TE 60 (02)	DRS-Y	96 dB (A)	107 dB (A)	14 m/s ²	1.5 m/s ²	15 min.	61 min.	concrete 40 N/mm	TE-YP-SM 28	12,9	52	7,75
TE 60 (03)	DRS-Y	96 dB (A)	107 dB (A)	15.5 m/s ²	1.5 m/s ²	12 min.	48 min.	concrete 40 N/mm	TE-YP-SM 28	11,5	46	8,70
TE 60-T-ATC (02)	DRS-Y	99 dB (A)	110 dB (A)	8.5 m/s ²	1.5 m/s ²	42 min.	168 min.	concrete 40 N/mm	TE-YP-SM 28	34	136	2,94
TE 60-ATC (03)	DRS-Y	101 dB (A)	112 dB (A)	10.5 m/s ²	1.5 m/s ²	27 min.	108 min.	concrete 40 N/mm	TE-YP-SM 28	25	100	4,00
TE 60-ATC-AVR (03)	DRS-Y	101 dB (A)	112 dB (A)	7 m/s ²	1.5 m/s ²	61 min.	244 min.	concrete 40 N/mm	TE-YP-SM 28	56,3	225	1,78
TE 70 (02)	DRS-Y	99 dB (A)	110 dB (A)	18 m/s ²	1.5 m/s ²	9 min.	37 min.	concrete 40 N/mm	TE-YP-SM 28	11,9	48	8,40
TE 70-AVR (03)	DRS-Y	102 dB (A)	113 dB (A)	9 m/s ²	1.5 m/s ²	37 min.	148 min.	concrete 40 N/mm	TE-YP-SM 28	51	204	1,96
TE 70-ATC/AVR (03)	DRS-Y	102 dB (A)	113 dB (A)	9 m/s ²	1.5 m/s ²	37 min.	148 min.	concrete 40 N/mm	TE-YP-SM 28	51	204	1,96
TE 76 (01)	DRS-Y	91 dB (A)	102 dB (A)	15 m/s ²	1.5 m/s ²	13 min.	53 min.	concrete 40 N/mm	TE-YP-SM 28	14,7	59	6,80
TE 80-ATC (01)	DRS-Y	99.5 dB (A)	110.5 dB (A)	8.5 m/s ²	1.5 m/s ²	42 min.	166 min.	concrete 40 N/mm	TE-YP-SM 28	56,5	225	1,77
TE 80-ATC/AVR (03)	DRS-Y	102 dB (A)	113 dB (A)	7 m/s ²	1.5 m/s ²	61 min.	244 min.	concrete 40 N/mm	TE-YP-SM 28	85	340	1,18

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Cordless Breakers - demolition

Basic tool data								Productivity data				
Tool	Dust removal available	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Volume till EAV (liter)	Volume till ELV (liter)	HSE points
TE 300-A36 (03)	no	88 dB (A)	99 dB (A)	7,9 m/s ²	1,5 m/s ²	48 min.	192 min.	concrete 50/60 N/mm ²	TE-C	20,6	82,56	4,85
TE 500-A36 (04)				6,7 m/s ²	1,5 m/s ²	67 min.	268 min.	concrete 50/60 N/mm ²	TE-Y	67	268	1,49

Breakers - chiseling to wall

Basic tool data								Productivity data				
Tool	Dust removal available	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Volume till EAV (liter)	Volume till ELV (liter)	HSE Points
TE 300-AVR (01)	no	91 dB (A)	102 dB (A)	13,5 m/s ²	1,5 m/s ²	16 min.	64 min.	concrete 40 N/mm ²	TE-YP-SM 28	5	20	20,00
TE 500 (01)	DRS-B	94 dB (A)	105 dB (A)	12,1 m/s ²	1,5 m/s ²	20 min.	82 min.	concrete 40 N/mm ²	TE-YP-SM 28	22,1	88	4,52
TE 500-AVR (01)	DRS-B	94 dB (A)	105 dB (A)	10,1 m/s ²	1,5 m/s ²	29 min.	118 min.	concrete 40 N/mm ²	TE-YP-SM 28	31,8	127	3,14
TE 500-AVR (03)	DRS-B	84 dB (A)	95 dB (A)	6,8 m/s ²	1,5 m/s ²	65 min.	260 min.	concrete 50/60 N/mm ²	TE-Y	65	260	1,54
TE 700-AVR (01)	DRS-B	86 dB (A)	97 dB (A)	6,5 m/s ²	1,5 m/s ²	71 min.	284 min.	concrete 40 N/mm ²	TE-YP-SM 28	60	240	1,67
TE 706 (01)	DRS-B	90 dB (A)	101 dB (A)	9 m/s ²	1,5 m/s ²	37 min.	148 min.	concrete 40 N/mm ²	TE-YP-SM 28	41,5	165	2,41
TE 706-AVR (01)	DRS-B	87 dB (A)	98 dB (A)	5,5 m/s ²	1,5 m/s ²	99 min.	397 min.	concrete 40 N/mm ²	TE-YP-SM 28	111,1	444	0,90
TE 800 (01)	DRS-B	87 dB (A)	98 dB (A)	16 m/s ²	1,5 m/s ²	12 min.	48 min.	concrete 40 N/mm ²	TE-SP-SM 36	25	100	4,00
TE 800-AVR (01)	DRS-B	87 dB (A)	98 dB (A)	9 m/s ²	1,5 m/s ²	37 min.	148 min.	concrete 40 N/mm ²	TE-SP-SM 36	95	380	1,05

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x. Uncertainty (k): noise 3dB.

Breakers - demolition on floor edge

Basic tool data								Productivity data				
Tool	Dust removal available	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Volume till EAV (liter)	Volume till ELV (liter)	HSE Points
TE 800 (01)	DRS-B	87 dB (A)	98 dB (A)	16 m/s ²	1,5 m/s ²	12 min.	48 min.	concrete 40 N/mm ²	TE-SP-SM 36	52	208	1,92
TE 800-AVR (01)	DRS-B	87 dB (A)	98 dB (A)	9 m/s ²	1,5 m/s ²	37 min.	148 min.	concrete 40 N/mm ²	TE-SP-SM 36	192	768	0,52
TE 905-AVR (01)	DRS-B	92 dB (A)	103 dB (A)	8,5 m/s ²	1,5 m/s ²	42 min.	166 min.	concrete 40 N/mm ²	TE-SP-SM 36	139,8	559	0,72
TE 1000-AVR (01)	DRS-B	87 dB (A)	98 dB (A)	6,5 m/s ²	1,5 m/s ²	71 min.	284 min.	concrete 40 N/mm ²	TE-SP-SM 36	325	1300	0,31
TE 1000-AVR (02)	DRS-B	85 dB (A)	96 dB (A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	concrete 40 N/mm ²	TE-SP-SM 36	900	3600	0,11
TE 1500-AVR (01)	DRS-B	89 dB (A)	100 dB (A)	12 m/s ²	1,5 m/s ²	21 min.	84 min.	concrete 40 N/mm ²	TE-SP-SM 36	145	580	0,69
TE 2000-AVR (01)	DRS-B	77 dB (A)	97 dB (A)	4,8 m/s ²	1,5 m/s ²	130 min.	521 min.	concrete 50/60 N/mm ²	TE-S	1846	7384	0,05
TE 3000-AVR (01)	DRS-B	94 dB (A)	105 dB (A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	concrete 40 N/mm ²	TE Hex 28	2075	8300	0,05

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

How to read the Tool Selector

Breaking - The volume of material that can be broken for a particular tool and given workpiece material and consumable in a working day before the EAV and ELV (shown in brackets) are given in the productivity data section.

The red value is the number of HSE points per litre for the given tool and application.

Drilling in steel
Cordless drill drivers, hammer drills drivers, compact drill drivers

Tool	Dust removal system	Basic tool data						Productivity data												
		Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²)										
										HSE Points per hole sheet steel thickness (mm) one-step drilling										
										1	2	3	4	5	6	7	8	9	10	
SF 2-A (01)	no	64 dB(A)	75 dB(A)	1.9 m/s ²	1.5 m/s ²	>440min	>1440 min.	mild steel	HSS Spiral drill 6,0x93	10320 (41280) 0,01	5120 (20480) 0,02	3440 (13760) 0,03	2560 (10240) 0,04	2000 (8000) 0,05	1680 (6720) 0,06	1440 (5760) 0,07	1280 (5120) 0,08	1120 (4480) 0,09	1040 (4160) 0,10	
SF 2-A12 (02)	no	72 dB(A)	83 dB(A)	3,7 m/s ²	1,5 m/s ²	219 min.	876 min.	mild steel												
SF 2H-A12 (02)	no	76 dB(A)	87 dB(A)	3,2 m/s ²	1,5 m/s ²	293 min.	956 min.	mild steel												
SF 6-A22 (01)	no	73 dB(A)	84 dB(A)	2 m/s ²	1.5 m/s ²	>440min	>1440 min.	mild steel	HSS Spiral drill 6,0x93	6640 (26560) 0,02	3280 (13120) 0,03	2160 (8640) 0,05	1600 (6400) 0,06	1280 (5120) 0,08	1040 (4160) 0,10	880 (3520) 0,11	800 (3200) 0,13	720 (2880) 0,14	640 (2560) 0,16	
SF 6H-A22 (01)	no	84 dB(A)	95 dB(A)	2 m/s ²	1.5 m/s ²	>440min	>1440 min.	mild steel	HSS Spiral drill 6,0x93	10320 (41280) 0,01	5120 (20480) 0,02	3440 (13760) 0,03	2560 (10240) 0,04	2000 (8000) 0,05	1680 (6720) 0,06	1440 (5760) 0,07	1280 (5120) 0,08	1120 (4480) 0,09	1040 (4160) 0,10	
SF 8M-A22 (01)	no	77 dB(A)	88 dB(A)	2.5 m/s ²	1.5 m/s ²	440min.	>1440 min.	mild steel	HSS Spiral drill 6,0x93	7680 (30720) 0,01	3840 (15360) 0,03	2560 (10240) 0,04	1920 (7680) 0,05	1530 (6120) 0,07	1280 (5120) 0,08	1090 (4360) 0,09	960 (3840) 0,10	850 (3400) 0,12	760 (3040) 0,13	
SF 10W (01)	no	75 dB(A)	86 dB(A)	2.5 m/s ²	1.5 m/s ²	440min.	>1440 min.	mild steel	HSS Spiral drill 6,0x93	7680 (30720) 0,01	3840 (15360) 0,03	2560 (10240) 0,04	1920 (7680) 0,05	1530 (6120) 0,07	1280 (5120) 0,08	1090 (4360) 0,09	960 (3840) 0,10	850 (3400) 0,12	760 (3040) 0,13	
SF 10W-A22 ATC (02)	no	75 dB(A)	86 dB(A)	2.5 m/s ²	1.5 m/s ²	440min.	>1440 min.	mild steel	HSS Spiral drill 6,0x93	7680 (30720) 0,01	3840 (15360) 0,03	2560 (10240) 0,04	1920 (7680) 0,05	1530 (6120) 0,07	1280 (5120) 0,08	1090 (4360) 0,09	960 (3840) 0,10	850 (3400) 0,12	760 (3040) 0,13	
SF 14-A (01)	no	75 dB(A)	86 dB(A)	2 m/s ²	1.5 m/s ²	>440min	>1440 min.	mild steel	HSS Spiral drill 6,0x93	11500 (46000) 0,01	5700 (22800) 0,02	3800 (15200) 0,03	2800 (11200) 0,04	2300 (9200) 0,04	1900 (7600) 0,05	1600 (6400) 0,06	1400 (5600) 0,07	1200 (4800) 0,08	1100 (4400) 0,09	
SF 22-A (01)	no	75 dB(A)	86 dB(A)	2 m/s ²	1.5 m/s ²	>440min	>1440 min.	mild steel	HSS Spiral drill 6,0x93	7680 (30720) 0,01	3840 (15360) 0,03	2560 (10240) 0,04	1920 (7680) 0,05	1530 (6120) 0,07	1280 (5120) 0,08	1090 (4360) 0,09	960 (3840) 0,10	850 (3400) 0,12	760 (3040) 0,13	
SFH 22-A (01)	no	75 dB(A)	86 dB(A)	2 m/s ²	1.5 m/s ²	>440min	>1440 min.	mild steel	HSS Spiral drill 6,0x93	8300 (33200) 0,01	4100 (16400) 0,02	2700 (10800) 0,04	2000 (8000) 0,05	1600 (6400) 0,06	1300 (5200) 0,08	1100 (4400) 0,09	1000 (4000) 0,10	900 (3600) 0,11	800 (3200) 0,13	
SFC 14-A (01)	no	69 dB(A)	80 dB(A)	2 m/s ²	1.5 m/s ²	>440min	>1440 min.	mild steel	HSS Spiral drill 6,0x93	12900 (51600) 0,01	6400 (25600) 0,02	4300 (17200) 0,02	3200 (12800) 0,03	2500 (10000) 0,04	2100 (8400) 0,05	1800 (7200) 0,06	1600 (6400) 0,06	1400 (5600) 0,07	1300 (5200) 0,08	
SFC 22-A (01)	no	69 dB(A)	80 dB(A)	2 m/s ²	1.5 m/s ²	>440min	>1440 min.	mild steel	HSS Spiral drill 6,0x93	22200 (88800) 0,00	11100 (44400) 0,01	7400 (29600) 0,01	5500 (22000) 0,02	4400 (17600) 0,02	3700 (14800) 0,03	3100 (12400) 0,03	2700 (10800) 0,04	2400 (9600) 0,04	2200 (8800) 0,05	
SFD 2-A (01)	no	64 dB(A)	75 dB(A)	1.9 m/s ²	1.5 m/s ²	>440min	>1440 min.	mild steel	HSS Spiral drill 6,0x93	10320 (41280) 0,01	5120 (20480) 0,02	3440 (13760) 0,03	2560 (10240) 0,04	2000 (8000) 0,05	1680 (6720) 0,06	1440 (5760) 0,07	1280 (5120) 0,08	1120 (4480) 0,09	1040 (4160) 0,10	

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (K): noise 3dB.

Drilling in steel
Electric drill driver

Basic tool data								Productivity data											
Tool	Dust removal system	Emission Sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value a _{hv} *	Uncertainty k	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) HSE Points per hole sheet steel thickness (mm) one-step drilling									
										1	2	3	4	5	6	7	8	9	10
UD 30 (01)	no	86 dB(A)	97 dB(A)	6 m/s ²	1.5 m/s ²	83 min.	332 min.	mild steel	HSS Spiral drill 6,0x93	3010	1500	1000	750	600	500	430	370	330	300
										(12040)	(6000)	(4000)	(3000)	(2400)	(2000)	(1480)	(1480)	(1320)	(1200)
										0,03	0,07	0,10	0,13	0,17	0,20	0,23	0,27	0,30	0,33
										3610	1800	1200	900	720	600	510	450	400	360
										(14440)	(7200)	(4800)	(3600)	(2880)	(2400)	(2040)	(1800)	(1600)	(1440)
										0,03	0,06	0,08	0,11	0,14	0,17	0,20	0,22	0,25	0,28
										4510	2250	1500	1120	900	750	640	560	500	450
										(18040)	(9000)	(6000)	(4480)	(3600)	(3000)	(2560)	(2240)	(2000)	(1800)
HSS Spiral drill 4,0x75	6020	3010	2000	1500	1200	1000	860	750	660	600									
	(24080)	(12040)	(8000)	(6000)	(4800)	(4000)	(3440)	(3000)	(2640)	(2400)									
	0,02	0,04	0,07	0,09	0,11	0,13	0,16	0,18	0,20	0,22									
	HSS Spiral drill 3,0x61	0,02	0,03	0,05	0,07	0,08	0,10	0,12	0,13	0,15	0,17								

* Emission sound pressure level L_{pA} and triaxial vibration value a_{hv} according to the relevant European Standard EN 60745-2-x. Uncertainty (k): noise 3dB.

Drilling in steel - electric rotary hammers

Basic tool data								Productivity data											
Tool	Dust removal system	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value a _{hv} *	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) HSE Points per hole sheet steel thickness (mm) one-step drilling									
										1	2	3	4	5	6	7	8	9	10
TE 2-M (02)	no	n.a.	n.a.	4.5 m/s ²	1.5 m/s ²	148 min.	592 min.	mild steel	HSS Spiral drill 6,0x93	3030	1510	1010	750	600	500	430	370	330	300
										(12120)	(6040)	(4040)	(3000)	(2400)	(2000)	(1720)	(1480)	(1320)	(1200)
										0,03	0,07	0,10	0,13	0,17	0,20	0,23	0,27	0,30	0,33

* Emission sound pressure level L_{pA} and triaxial vibration value a_{hv} according to the relevant European Standard EN 60745-2-x. Uncertainty (k): noise 3dB.

Drilling in steel - cordless rotary Hammers

Basic tool data								Productivity data											
Tool	Dust removal system	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value a _{hv} *	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) HSE Points per hole sheet steel thickness (mm) one-step drilling									
										1	2	3	4	5	6	7	8	9	10
TE 4-A22 (01)	no	n.a.	n.a.	5.5 m/s ²	1.5 m/s ²	99 min.	396 min.	mild steel	HSS Spiral drill 6,0x93	3070	1530	1020	760	610	510	430	380	340	300
										(12280)	(6120)	(4080)	(3040)	(2440)	(2040)	(1720)	(1520)	(1360)	(1200)
										0,03	0,07	0,10	0,13	0,16	0,20	0,23	0,26	0,29	0,33
TE 6-A36-AVR (03)	no	n.a.	n.a.	2.5 m/s ²	1.5 m/s ²	440 min.	>1440 min.	mild steel	HSS Spiral drill 6,0x93	7320	3660	2440	1830	1460	1220	1040	910	810	730
										(29280)	(14640)	(9760)	(7320)	(5840)	(4880)	(4160)	(3640)	(3240)	(2920)
										0,01	0,03	0,04	0,05	0,07	0,08	0,10	0,11	0,12	0,14
TE 30-A36 (02)	no	n.a.	n.a.	3 m/s ²	1.5 m/s ²	333 min.	1332 min.	mild steel	HSS Spiral drill 6,0x93	7110	3550	2370	1770	1420	1180	1010	880	790	710
										(28440)	(14200)	(9480)	(7080)	(5680)	(4720)	(4040)	(3520)	(3160)	(2840)
										0,01	0,03	0,04	0,06	0,07	0,08	0,10	0,11	0,13	0,14
								mild steel	HSS Spiral drill 5,0 x 86	8540	4270	2840	2130	1700	1420	1220	1060	940	850
										(34160)	(17080)	(11360)	(8520)	(6800)	(5680)	(4880)	(4240)	(3760)	(3400)
										0,01	0,02	0,04	0,05	0,06	0,07	0,08	0,09	0,11	0,12
								mild steel	HSS Spiral drill 4,0 x 75	10670	5330	3550	2660	2130	1770	1520	1330	1180	1060
										(42680)	(21320)	(14200)	(10640)	(8520)	(7080)	(6080)	(5320)	(4720)	(4240)
mild steel	HSS Spiral drill 3,0 x 61	14230	7110	4740	3550	2840	2370	2030	1770	1580	1420								
		(56920)	(28440)	(18960)	(14200)	(11360)	(9480)	(8120)	(7080)	(6320)	(5680)								
		0,01	0,01	0,02	0,03	0,04	0,04	0,05	0,06	0,06	0,07								

* Emission sound pressure level L_{pA} and triaxial vibration value a_{hv} according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Rotary hammers

Basic tool data								Productivity data									
Tool	Dust removal system	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value a _{hv} *	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²)							
										HSE Points per hole sheet steel thickness (mm) pre drilling (6mm pre-hole)							
										3	4	5	6	7	8	9	10
TE 4-A22 (01)	no	n.a.	n.a.	5.5 m/s ²	1.5 m/s ²	99 min.	396 min.	mild steel	HSS Spiral drill 12,0 x 151	270	200	160	130	110	100	90	80
										(1080)	(800)	(640)	(520)	(440)	(400)	(360)	(320)
										0,37	0,50	0,63	0,77	0,91	1,00	1,11	1,25
										290	220	170	140	120	110	90	80
										(1160)	(880)	(680)	(560)	(480)	(440)	(360)	(320)
										0,34	0,45	0,59	0,71	0,83	0,91	1,11	1,25
TE 6-A36-AVR (03)	no	n.a.	n.a.	2.5 m/s ²	1.5 m/s ²	440 min.	>1440 min	mild steel	HSS Spiral drill 12,0 x 151	320	240	190	160	140	120	100	90
										(1280)	(960)	(760)	(640)	(560)	(480)	(400)	(360)
										0,31	0,42	0,53	0,63	0,71	0,83	1,00	1,11
										360	270	210	180	150	130	120	100
										(1440)	(1080)	(840)	(720)	(600)	(520)	(480)	(400)
										0,28	0,37	0,48	0,56	0,67	0,77	0,83	1,00
TE 2-M (02)	no	n.a.	n.a.	4.5 m/s ²	1.5 m/s ²	148 min.	592 min.	mild steel	HSS Spiral drill 10,0 x 133	410	300	240	200	170	150	130	120
										(1640)	(1200)	(960)	(800)	(680)	(600)	(520)	(480)
										0,24	0,33	0,42	0,50	0,59	0,67	0,77	0,83
										550	410	330	270	230	200	180	160
										(2200)	(1640)	(1320)	(1080)	(920)	(800)	(720)	(640)
										0,18	0,24	0,30	0,37	0,43	0,50	0,56	0,63
TE 30-A36 (02)	no	n.a.	n.a.	3 m/s ²	1.5 m/s ²	333 min.	1332 min.	mild steel	HSS Spiral drill 11,0 x 142	600	450	360	300	260	220	200	180
										(2400)	(1800)	(1440)	(1200)	(1040)	(880)	(800)	(720)
										0,17	0,22	0,28	0,33	0,38	0,45	0,50	0,56
										660	500	400	330	280	250	220	200
										(2640)	(2000)	(1600)	(1320)	(1120)	(1000)	(880)	(800)
										0,15	0,20	0,25	0,30	0,36	0,40	0,45	0,50
TE 2-M (02)	no	n.a.	n.a.	4.5 m/s ²	1.5 m/s ²	148 min.	592 min.	mild steel	HSS Spiral drill 9,0 x 125	740	550	440	370	310	270	240	220
										(2960)	(2200)	(1760)	(1480)	(1240)	(1080)	(960)	(880)
										0,14	0,18	0,23	0,27	0,32	0,37	0,42	0,45
										830	620	500	410	350	310	270	250
										(3320)	(2480)	(2000)	(1640)	(1400)	(1240)	(1080)	(1000)
										0,12	0,16	0,20	0,24	0,29	0,32	0,37	0,40
TE 2-M (02)	no	n.a.	n.a.	4.5 m/s ²	1.5 m/s ²	148 min.	592 min.	mild steel	HSS Spiral drill 8,0 x 117	80	60	50	40	30	30	20	20
										(320)	(240)	(200)	(160)	(120)	(120)	(80)	(80)
										1,25	1,67	2,00	2,50	3,33	3,33	5,00	5,00
										90	60	50	40	30	30	30	20
										(360)	(240)	(200)	(160)	(120)	(120)	(120)	(80)
										1,11	1,67	2,00	2,50	3,33	3,33	3,33	5,00
TE 2-M (02)	no	n.a.	n.a.	4.5 m/s ²	1.5 m/s ²	148 min.	592 min.	mild steel	HSS Spiral drill 10,0 x 133	100	70	60	50	40	30	30	30
										(400)	(280)	(240)	(200)	(160)	(120)	(120)	(120)
										1,00	1,43	1,67	2,00	2,50	3,33	3,33	3,33
										110	80	60	50	40	40	30	30
										(440)	(320)	(240)	(200)	(160)	(160)	(120)	(120)
										0,91	1,25	1,67	2,00	2,50	2,50	3,33	3,33
TE 2-M (02)	no	n.a.	n.a.	4.5 m/s ²	1.5 m/s ²	148 min.	592 min.	mild steel	HSS Spiral drill 8,0 x 117	120	90	70	60	50	40	40	30
										(480)	(360)	(280)	(240)	(200)	(160)	(160)	(120)
										0,83	1,11	1,43	1,67	2,00	2,50	2,50	3,33
										430	320	260	210	180	160	140	130
										(1720)	(1280)	(1040)	(840)	(720)	(640)	(560)	(520)
										0,23	0,31	0,38	0,48	0,56	0,63	0,71	0,77
TE 30-A36 (02)	no	n.a.	n.a.	3 m/s ²	1.5 m/s ²	333 min.	1332 min.	mild steel	HSS Spiral drill 11,0 x 142	470	350	280	230	200	170	150	140
										(1880)	(1400)	(1120)	(920)	(800)	(680)	(600)	(560)
										0,21	0,29	0,36	0,43	0,50	0,59	0,67	0,71
										520	390	310	260	220	190	170	150
										(2080)	(1560)	(1240)	(1040)	(880)	(760)	(680)	(600)
										0,19	0,26	0,32	0,38	0,45	0,53	0,59	0,67
TE 30-A36 (02)	no	n.a.	n.a.	3 m/s ²	1.5 m/s ²	333 min.	1332 min.	mild steel	HSS Spiral drill 10,0 x 133	580	430	340	290	240	210	190	170
										(2320)	(1720)	(1360)	(1160)	(960)	(840)	(760)	(680)
										0,17	0,23	0,29	0,34	0,42	0,48	0,53	0,59
										650	490	390	320	280	240	210	190
										(2600)	(1960)	(1560)	(1280)	(1120)	(960)	(840)	(760)
										0,15	0,20	0,26	0,31	0,36	0,42	0,48	0,53

* Emission sound pressure level L_{pA} and triaxial vibration value a_{hv} according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Rotary hammers

Basic tool data								Productivity data					
Tool	Dust removal system	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value a _{hV} *	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) HSE Points per hole consumable diameter metal hole saw in mm			
										25	32	40	51
TE 4-A22 (01)	no	n.a.	n.a.	5.5 m/s ²	1.5 m/s ²	99 min.	396 min.	2 mm mild steel	Metal Hole Saw	180	180	110	110
										(720)	(720)	(440)	(440)
										0,56	0,56	0,91	0,91
TE 6-A36-AVR (03)	no	n.a.	n.a.	2.5 m/s ²	1.5 m/s ²	440 min.	>1440 min.	2 mm mild steel	Metal Hole Saw	290	290	180	180
										(1160)	(1160)	(720)	(720)
										0,34	0,34	0,56	0,56
TE 2-M (02)	no	n.a.	n.a.	4.5 m/s ²	1.5 m/s ²	148 min.	592 min.	2 mm mild steel	Metal Hole Saw	90	90	80	80
										(360)	(360)	(320)	(320)
										1,11	1,11	1,25	1,25
TE 30-A36 (02)	no	n.a.	n.a.	3 m/s ²	1.5 m/s ²	333 min.	1332 min.	2 mm mild steel	Metal Hole Saw	510			290
											(2040)		(1160)
											0,20		0,34

* Emission sound pressure level L_{pA} and triaxial vibration value a_{hV} according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Drilling in concrete
Cordless drill/drivers

Basic tool data								Productivity data				
Tool	Dust removal system	Emission Sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5.0 m/s ²)		
										HSE points per hole		
										Hole depth: 50 mm Drilling diameter: 8 mm	80 mm 10 mm	90 mm 12 mm
SFH 22-A (01)	no	91 dB(A)	102 dB(A)	12 m/s ²	1.5 m/s ²	21 min.	84 min.	Screed concrete	Masonry bit	300 (1200) 0,33	150 (600) 0,67	95 (380) 1,05
	no	91 dB(A)	102 dB(A)	12 m/s ²	1.5 m/s ²	21 min.	84 min.	Sand-limestone (density 2.0)	Masonry bit	360 (1440) 0,28	140 (560) 0,71	80 (320) 1,25
SFH 144-A (01)	no	91 dB(A)	102 dB(A)	12 m/s ²	1.5 m/s ²	21 min.	84 min.	Screed concrete	Masonry bit	330 (1320) 0,30	140 (560) 0,71	110 (440) 0,91
	no	91 dB(A)	102 dB(A)	12 m/s ²	1.5 m/s ²	21 min.	84 min.	Sand-limestone (density 2.0)	Masonry bit	270 (1080) 0,37	110 (440) 0,91	55 (220) 1,82
SFH 151-A (01)	no	93 dB(A)	104 dB(A)	11.8 m/s ²	1.5 m/s ²	22 min.	88 min.	Screed concrete	Masonry bit	250 (1000) 0,40	140 (560) 0,71	70 (280) 1,43
	no	93 dB(A)	104 dB(A)	11.8 m/s ²	1.5 m/s ²	22 min.	88 min.	Sand-limestone (density 2.0)	Masonry bit	330 (1320) 0,30	135 (540) 0,74	70 (280) 1,43
SFH 181-A (01)	no	91 dB(A)	102 dB(A)	13.1 m/s ²	1.5 m/s ²	17 min.	68 min.	Screed concrete	Masonry bit	260 (1040) 0,38	140 (560) 0,71	90 (360) 1,11
	no	91 dB(A)	102 dB(A)	13.1 m/s ²	1.5 m/s ²	17 min.	68 min.	Sand-limestone (density 2.0)	Masonry bit	500 (2000) 0,20	180 (720) 0,56	90 (360) 1,11

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Universal hammers

Basic tool data								Productivity data				
Tool	Dust removal system	Emission Sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Work piece material of productivity data	Consumable	Number of holes to EAV 2.5 m/s ² (ELV 5.0 m/s ²)		
										HSE points per hole		
										Hole depth: 50 mm Drilling diameter: 8 mm	80 mm 10 mm	90 mm 12 mm
UH 240-A (01)	no	93 dB(A)	104 dB(A)	13.9 m/s ²	1.5 m/s ²	16 min.	64 min.	Screed concrete	Masonry bit	210 (840) 0,48	150 (600) 0,67	120 (480) 0,83
	no	93 dB(A)	104 dB(A)	13.9 m/s ²	1.5 m/s ²	16 min.	64 min.	Sand-limestone (density 2.0)	Masonry bit	370 (1480) 0,27	170 (680) 0,59	85 (340) 1,18
UH 650 (01)	no	96 dB(A)	107 dB(A)	14 m/s ²	1.5 m/s ²	15 min.	60 min.	Screed concrete	Masonry bit	260 (1040) 0,38	140 (560) 0,71	70 (280) 1,43
	no	96 dB(A)	107 dB(A)	14 m/s ²	1.5 m/s ²	15 min.	60 min.	Sand-limestone (density 2.0)	Masonry bit	280 (1120) 0,36	115 (460) 0,87	45 (180) 2,22

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Impact Fastening - Impact drivers/wrenches

Basic tool data								Productivity data			
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Work piece material of productivity data	Screw type	Number of screw settings to EAV 2.5 m/s ² (ELV 5 m/s ²)	HSE points per screw setting
SI 100 (01)	no	95 dB(A)	106 dB(A)	8.4 m/s ²	1.5 m/s ²	43 min.	172 min.	concrete	HUS H 12.5 (10 mm)	635 (2540)	0,16
SID 2-A12 (02)	no	72 dB(A)	83 dB(A)	1,5 m/s ²	1,5 m/s ²	>440 min.	>1440 min.	concrete	n/a	n/a	n/a
SID 2-A (01)	no	92 dB(A)	103 dB(A)	16.5 m/s ²	1.5 m/s ²	11 min.	44 min.	steel	M12 metal screw	888 (3552)	0,11
				16.5 m/s ²	1.5 m/s ²	11 min.	44 min.	concrete	HUS H 7.5 screw (6 mm)	481 (1924)	0,21
SID 4-A22 (01)	no	87 dB(A)	98 dB(A)	12 m/s ²	1.5 m/s ²	21 min.	83 min.	steel	M12 metal screw	592 (2368)	0,17
				12 m/s ²	1.5 m/s ²	21 min.	83 min.	concrete	HUS H 7.5 screw (6 mm)	296 (1184)	0,34
SIW 6AT-A22 (01)	no	95 dB(A)	106 dB(A)	13.5 m/s ²	1.5 m/s ²	16 min.	66 min.	steel	M12 metal screw	740 (2960)	0,14
SID 8-A (01)	no	95 dB(A)	106 dB(A)	13.5 m/s ²	1.5 m/s ²	16 min.	66 min.	concrete	n/a	n/a	n/a
SID/SIW 14-A (01)	no	94 dB(A)	83 dB(A)	7.5 m/s ²	1.5 m/s ²	53 min.	212 min.	steel	M12 metal screw	1600 (6400)	0,06
				7.5 m/s ²	1.5 m/s ²	53 min.	212 min.	concrete	HUS H 6 screw (6 mm)	800 (3200)	0,13
SID/SIW 22-A (01)	no	86 dB(A)	97 dB(A)	11 m/s ²	1.5 m/s ²	25 min.	100 min.	steel	M12 metal screw	740 (2960)	0,14
				11 m/s ²	1.5 m/s ²	25 min.	100 min.	concrete	HUS H 7.5 screw (6 mm)	370 (1480)	0,27
SID/SIW 121-A (01)	no	85 dB(A)	96 dB(A)	7.4 m/s ²	1.5 m/s ²	55 min.	220 min.	steel	M12 metal	1600 (6400)	0,06
SID/SIW 144-A (01)	no	93 dB(A)	104 dB(A)	12 m/s ²	1.5 m/s ²	21 min.	84 min.	steel	M12 metal	625 (2500)	0,16
				12 m/s ²	1.5 m/s ²	21 min.	84 min.	concrete	HUS H 7.5 (6 mm)	300 (1200)	0,33
SIW 22T-A (01)	no	97 dB(A)	108 dB(A)	14.5 m/s ²	1.5 m/s ²	14 min.	56 min.	steel	M20 metal	420 (1680)	0,24
				14.5 m/s ²	1.5 m/s ²	14 min.	56 min.	concrete	HUS H 10.5 (8 mm)	170 (680)	0,59
				14.5 m/s ²	1.5 m/s ²	14 min.	56 min.	concrete	HUS H 12.5 (10 mm)	110 (440)	0,91
				14.5 m/s ²	1.5 m/s ²	14 min.	56 min.	concrete	HUS H 16.5 (14 mm)	70 (280)	1,43
				14.5 m/s ²	1.5 m/s ²	14 min.	56 min.	wood	12 X wood (240 mm)	22 (88)	4,55

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Screwdrivers

Basic tool data								Productivity data			
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Work piece material of productivity data	Screw type	Number of screw settings to EAV 2.5 m/s ² (ELV 5 m/s ²)	HSE points per screw setting
TKI 2500 (01)	no	97 dB(A)	108 dB(A)	12.3 m/s ²	1.5 m/s ²	20 min.	80 min.	steel	M10 metal	590 (2360)	0,17
				12.3 m/s ²	1.5 m/s ²	20 min.	80 min.	concrete	HUS H 7.5 (6 mm)	290 (1160)	0,34
ST 1800 (01)	no	84 dB(A)	95 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	1 mm metal sheet	S-MD 01Z 4,8 x 19	2500 (10000)	0,04
				2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	overlap mount 1 mm to 1 mm	S-MD 51Z 4,8 x 19	2100 (8400)	0,05
				2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	1 mm metal sheet	S-MD 03Z 5,5 x 25	800 (3200)	0,13
				2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	mount on 4 mm steel beam	S-MD 53Z 5,5 x 25	900 (3600)	0,11
				2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	1 mm metal sheet	S-MD 05Z 5,5 x 40	280 (1120)	0,36
ST 1800-A22 (01)	no	70 dB(A)	81 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	mount on 10 mm steel beam	S-MD 55Z 5,5 x 45	330 (1320)	0,30
				0.5 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	1 mm metal sheet overlap mount 1 mm to 1 mm	S-MD 01Z 4,8 x 19	3000 (12000)	0,03
				0.5 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	to 1 mm	S-MD 51Z 4,8 x 19	5200 (20800)	0,02
				0.5 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	1 mm metal sheet	S-MD 03Z 5,5 x 25	1500 (6000)	0,07
				0.5 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	mount on 4 mm steel beam	S-MD 53Z 5,5 x 25	2700 (10800)	0,04
				0.5 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	1 mm metal sheet	S-MD 05Z 5,5 x 40	540 (2160)	0,19
SD 5000 (01)	no	85 dB(A)	96 dB(A)	3.4 m/s ²	1.5 m/s ²	260 min.	>1440 min.	mount on 10 mm steel beam	S-MD 55Z 5,5 x 45	800 (3200)	0,13
SD 5000-A22 (01)	no	71 dB(A)	82 dB(A)	2.5 m/s ²	1.5 m/s ²	440 min.	>1440 min.				
SD 6000 (01)	no	85 dB(A)	96 dB(A)	2.8 m/s ²	1.5 m/s ²	383 min.	>1440 min.				

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Diamond coring tools
Hand-held diamond core drilling with water in non reinforced concrete

Basic tool data								Productivity data									
Tool	Dust removal system	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value a _{hv} *	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Core bit length or type	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for coring diameter [mm] HSE points per hole Hole depth 100 mm							
										12	16	18	20	24	28	35	52
DD EC 1 (01)	wet	87 dB(A)	98 dB(A)	10 m/s ²	1.5 m/s ²	30 min.	120 min.	concrete 40 N/mm ²	150 mm	120 (480) 0,83		110 (440) 0,91	100 (400) 1,00				
				17 m/s ²						10 min.		40 min.	47 (188) 2,13				
DD 30-W (01)	wet	87 dB(A)	98 dB(A)	6 m/s ² 8 m/s ²	1.5 m/s ²	83 min.	333 min.	concrete 50/60 N/mm ²	SPX-T SPX-T abrasive								
DD 130 (01)	wet	89 dB(A)	100 dB(A)	5 m/s ²	1.5 m/s ²	120 min.	480 min.	concrete 40 N/mm ²	HWC				90 (360) 1,11				40 (160) 2,50
DD 150-U (01)	wet	87 dB(A)	98 dB(A)	7 m/s ²	1.5 m/s ²	61 min.	244 min.	concrete 40 N/mm ²	HWC 66/350								30 (120) 3,33

* Emission sound pressure level L_{pA} and triaxial vibration value a_{hv} according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Hand-held dry diamond core drilling into sand-limestone

Basic tool data								Productivity data																													
Tool	Dust removal system	Emission sound pressure level L _{pA} *	Emission sound power level*	Triaxial vibration value a _{hv} *	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Core bit length or type	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for coring diameter [mm] HSE points per hole Hole depth 100 mm																											
										20	24	28	35	52	67	68	87	102	112	122	132	152	162														
DD 110-D (01)	dry, vacuum	84 dB(A)	95 dB(A)	5.8 m/s ²	1.5 m/s ²	89 min.	356 min.	sand-limestone, density 2.0	SC HDMU							230 (920) 0,43								200 (800) 0,50						90 (360) 1,11							20 (80) 5,00
DD 130 (01)	dry, vacuum	89 dB(A)	100 dB(A)	6 m/s ²	1.5 m/s ²	83 min.	332 min.	sand-limestone, density 2.0	SC HDMU							370 (1480) 0,27									170 (680) 0,59						100 (400) 1,00						30 (120) 3,33
DD 150-U (01)	dry, vacuum	87 dB(A)	98 dB(A)	6.5 m/s ²	1.6 m/s ²	71 min.	284 min.	sand-limestone, density 2.0	DD-B HDMU							370 (1480) 0,27									170 (680) 0,59						100 (400) 1,00						30 (120) 3,33
				14.5 m/s ²	4.5 m/s ²	14 min.	56 min.	sand-limestone, density 2.0	DD-B PCM									280 (1120) 0,36																			

* Emission sound pressure level L_{pA} and triaxial vibration value a_{hv} according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

How to read the Tool Selector
Diamond coring

The number of holes that can be made for a particular tool given diameter, depth, work piece material and consumable in one working day before reaching the Core EAV and ELV (shown in brackets) are given under the productivity data. The red value is the number of HSE points per hole for the given application.

Diamond coring tools

Hand-held dry diamond socket cutting into sand-limestone

Basic tool data								Productivity data			
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Core bit length or type	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for coring diameter [mm] HSE points per hole Hole depth 60 mm	
										68	82
DD 110-D (01)	dry, vacuum	84 dB(A)	95 dB(A)	5.8 m/s ²	1.5 m/s ²	89 min.	356 min.	sand-limestone, density 2.0	SC HDMU	320	(1280)
				12 m/s ²						0,31	
DD 130 (01)	dry, vacuum	89 dB(A)	100 dB(A)	6 m/s ²	1.5 m/s ²	83 min.	332 min.	sand-limestone, density 2.0	SC HDMU	130	(520)
				11 m/s ²						0,77	
										280	(1120)
										190	(760)
										0,53	

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB.

Rig based diamond core drilling with water in non reinforced concrete (I)

Basic tool data								Productivity data								
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Core bit length or type	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for coring diameter [mm] HSE points per hole Hole depth 100 mm						
										8	12	16	18	20	24	28
DD EC1- (DD-CR1 Rig) (01)	wet	84 dB(A)	97 dB(A)	7 m/s ²	1.5 m/s ²	61 min.	244 min.	concrete 40 N/mm ²	DD-C 20/150 T2	110	(440)	0,91				
				11 m/s ²						65						
										(260)						
										1,54						

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 61029-2-6. Uncertainty (k): noise 3dB.

Rig based diamond core drilling with water in non reinforced concrete (II)

Basic tool data								Productivity data								
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Core bit length or type	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for coring diameter [mm] HSE points per hole Hole depth 200 mm						
										52	102	112	122	132	152	
DD 120 (01)	wet	89 dB(A)	102 dB(A)	2.5 m/s ²	n.a.	480 min.	>1440 min.	concrete 40 N/mm ²	DD BI...P2/PU	170	130	60	(240)	1,67		40
										(680)	(520)					
DD 130-Rig (01)	wet	89 dB(A)	102 dB(A)	3.5 m/s ²	n.a.	245 min.	980 min.	concrete 40 N/mm ²	DD BI...P2/P130	290	80	70	(280)	1,43		30
										(1160)	(320)					
										0,34	1,25					3,33

* Emission sound pressure level L_{pA} and triaxial vibration value ahv according to the relevant European Standard EN 61029-2-6. Uncertainty (k): noise 3dB.

Diamond grinding (minerals)

Basic tool data								Productivity data		
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Abrasion power to EAV 2,5 m/s ² (ELV 5m/s ²) HSE Points per cm ³	
									EAV	ELV
DG 150 (01)	integrated	88 dB(A)	99 dB(A)	5.8 m/s ²	1.5 m/s ²	89 min.	356 min.	concrete 40 N/mm ³	4806 cm ³	19224 cm ³

*Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-X or EN62841-2-X.

Diamond coring tools

Rig based diamond core drilling with water in non reinforced concrete (III)

Basic tool data								Productivity data									
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Work piece material of productivity data	Core bit length or type	Number of holes to EAV 2.5 m/s ² (ELV 5 m/s ²) for coring diameter [mm] HSE points per hole Hole depth 200 mm							
										35	82	102	112	132	152	162	202
DD 150-U-Rig*** (01)	wet	93 dB(A)	104 dB(A)	3.5 m/s ²	1.5 m/s ²	245 min.	980 min.	concrete 40 N/mm ²	DD-BI 102/430 P130	270 (408) 0,37							
									DD-BI 132/430 P130			95 (380) 1,05					
									DD-BI 162/320 PU						105 (420) 0,95		
DD 160 (02)	wet	93 dB(A)	106 dB(A)	4 m/s ²	1.5 m/s ²	188 min.	752 min.	concrete 40 N/mm ²	DD-BI 35/430 P4	700 (2800) 0,14							
									DD-BI 82/430 P		270 (1080) 0,37						
									DD-BI 152/430 P130					54 (216) 1,85			
									DD-BI 202/430 P2						90 (360) 1,11		
DD 200 (01)	wet	92 dB(A)	105 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	concrete 40 N/mm ²	DD-BL 112/500 H2	390 (1560) 0,26							
									DD-BL 202/500 H2						90 (360) 1,11		
DD 200 (02)	wet	93 dB(A)	109 dB(A)	2,5 m/s ²	1.5 m/s ²	480 min.	1920 min.	concrete 50/60 N/mm ²	DD-B HCL DD-B HCS DD-B UCL								
DD 250 (01)	wet	93 dB(A)	109 dB(A)	2,5 m/s ²	1.5 m/s ²	480 min.	1920 min.	concrete 50/60 N/mm ²	DD-B HCL DD-B HCS DD-B UCL								
DD 350 (01)	wet	95 dB(A)	108 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	concrete 40 N/mm ²	DD-BL 112/500 H2	1100 (4400) 0,09							
									DD-BL 202/500 H2						290 (1160) 0,34		
DD 350 - CA (01)	wet	95 dB(A)	108 dB(A)	<2.5 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	concrete 40 N/mm ²									
DD 500-Rig** (01)	wet	100 dB(A)	115 dB(A)	4.5 m/s ²	1.5 m/s ²	148 min.	592 min.	concrete 40 N/mm ²	DD BL 112/500 HX2S	700 (2800) 0,14							
									DD BL 202/500 HX2S						300 (1200) 0,33		
DD 500-Rig**- CA (01)	wet	100 dB(A)	115 dB(A)	<2.5 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	concrete 40 N/mm ²									

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 61029-2-6. Uncertainty (k): noise 3dB.

** Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 12348. Uncertainty (k) for sound pressure level LpA 4 dB(A). Uncertainty (k) for sound power level 2.5 dB(A).

*** Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745 or EN62841-2-X.

Diamond cutting tools - cutting

Basic tool data								Productivity data				
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Cutting Wheel	Application & Work piece material of productivity data	Meters / cuts till EAV 2.5 m/s ²	Meters till ELV 5 m/s ²	HSE Points
DCH 230 (01)	integrated	102.5 dB(A)	113.5 dB(A)	4.7 m/s ²	1.5 m/s ²	136 min.	544 min.	DC-D 230 C1	cutting off 50 mm concrete pavement slabs (5 cm x 40 cm slab)	70m	280m	1,43
DCH 300 (01)	integrated	106 dB(A)	117 dB(A)	5.1 m/s ²	1.5 m/s ²	115 min.	460 min.	DCH-D 305-C1	cutting off 50 mm concrete pavement slabs (5 cm x 40 cm slab)	61m	244m	1,64
DSH 600 (-X) (01)	Water suppression	102 dB(A)	115 dB(A)	2,5 m/s ²	1,5 m/s ²	480 min.	1920 min.	SPX Universal	cutting off 50/60 mm concrete pavement slabs	271 cuts	1084 cuts	0,37
DSH 700 (-X) (30 cm/12") (01)	Water suppression	99 dB(A)	108 dB(A)	4,7 m/s ²	1,5 m/s ²	148 min.	593 min.	SPX Universal	cutting off 50/60 mm concrete pavement slabs	90 cuts	370 cuts	1,11
DSH 900-X (35 cm/14") (01)	Water suppression	102 dB(A)	112 dB(A)	front 6.3 m/s ² rear 6.2 m/s ²	1.5 m/s ²	76 min.	302 min.	SPX Universal	cutting off 50/60 mm concrete pavement slabs			
DSH 900-X (40 cm/16") (01)	Water suppression	102 dB(A)	112 dB(A)	front 5.2 m/s ² rear 4.5 m/s ²	1.5 m/s ²	111 min.	444 min.	SP Universal EQD SPX Silent Asphalt AC-D GS	cutting off 50/60 mm concrete pavement slabs			

* Emission sound pressure level LpA and triaxial vibration value ahv according to EN 60745-2-x or EN62841-2-X (Uncertainty (k): noise 3 dB(A), vibration 1,52,7 m/s² , depending on tool and application).

Diamond cutting tools
Wall chasing / slitting

Basic tool data								Productivity data				
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Cutting Wheel	Application & Work piece material of productivity data	Meters till EAV 2.5 m/s ²	Meters till ELV 5 m/s ²	HSE Points
DC-SE 20 (01)	integrated	100 dB(A)	111 dB(A)	4.5 m/s ²	1.5 m/s ²	148 min.	592 min.	DC-D 125-SE M1	wall chasing 30 mm deep in sand-limestone	25,5	101	3,92
								DC-D 125-SE C1	wall chasing 30 mm deep in 40 N/mm ² concrete	86	344	1,16
DSH 700 30 (01)	Water suppression	99 dB(A)	110 dB(A)	4.5 m/s ²	2.4 m/s ²	148 min.	592 min.	DC-D 300/3.2/20 C1	cutting grooves 45 mm deep in 40 N/mm ² concrete	60	240	1,67
								DC-D 300/3.2/20 C1	cutting grooves 90 mm deep in sand-limestone (density 2.1)	110	440	0,91
								DC-D 300/3.2/20 C1	cutting 5 cm x 40 cm concrete pavement slab	135	540	0,74
DCH 180 SL (01)	integrated	106 dB(A)	117 dB(A)	5.6 m/s ²	1.7 m/s ²	96 min.	384 min.	DCH-D 185-SE M1	wall chasing 45 mm deep in sand-limestone	78,5	316	1,27
								DCH-D 185-SE C1	wall chasing 45 mm deep in 40 N/mm ² concrete	32	128	3,13
DCH 300 (01)	integrated	106 dB(A)	117 dB(A)	8 m/s ²	1.5 m/s ²	115 min.	460 min.	DCH-D 305-C1	cutting grooves 45 mm deep in 40 N/mm ² concrete	48	192	2,08
								DCH-D 305-M1	cutting grooves 45 mm deep in sand-limestone (density 2.0)	32	128	3,13
								DCH-D 305-M1	cutting grooves 90 mm deep in sand-limestone (density 2.0)	26	104	3,85
DCH 230 (01)	integrated	102.5 dB(A)	113.5 dB(A)	6.5 m/s ²	1.5 m/s ²	n/a	n/a	DC-D 230 C1	cutting grooves 45 mm deep in 40 N/mm ² concrete	58	232	1,72
								DC-D 230-M1	cutting grooves 50 mm deep in sand-limestone (density 2.1)	109	436	0,92

* Emission sound pressure level LpA and triaxial vibration value ahv according to EN 60745-2-x or EN62841-2-X (Uncertainty (k): noise 3 dB(A), vibration 1,52,7 m/s², depending on tool and application).

Angle grinders
Grinding steel

Basic tool data								Productivity data				
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material of productivity data	Metres till EAV 2.5 m/s ²	Metres till ELV 5 m/s ²	HSE Points
AG 125-S (01)	n/a	88 dB(A)	99 dB(A)	5.2 m/s ²	1.5 m/s ²	111 min.	444 min.	AG-D 125 USP 6,4	grinding 5x5 mm chamfer (12.5 mm ² on mild steel)	21	84	4,76
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4.6 m/s ²	1.5 m/s ²	142 min.	568 min.	AG-D 125 USP 6,4	grinding 5x5 mm chamfer (12.5 mm ² on mild steel)	28	112	3,57
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1.5 m/s ²	61 min.	244 min.	AG-D 125 USP 6,4	grinding 5x5 mm chamfer (12.5 mm ² on mild steel)	46	184	2,17
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5.7 m/s ²	1.5 m/s ²	92 min.	368 min.	AG-D 125 USP 6,4	grinding 5x5 mm chamfer (12.5 mm ² on mild steel)	50	200	2,00
AG 125-15DB (04)	DC-EX	91 dB(A)	102 dB(A)	4.4 m/s ²	1.5 m/s ²	155 min.	620 min.					
AG 125-19SE (04)	DC-EX	92 dB(A)	103 dB(A)	4.9 m/s ²	1.5 m/s ²	125 min.	500 min.					
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5.8 m/s ²	1.5 m/s ²	89 min.	356 min.	AG-D 230 USP 6,4	grinding 5x5 mm chamfer (12.5 mm ² on mild steel)	11	44	9,09
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1.5 m/s ²	120 min.	480 min.	AG-D 230 USP 6,4	grinding 5x5 mm chamfer (12.5 mm ² on mild steel)	61	244	1,64

* Emission sound pressure level LpA and triaxial vibration value ahv according to EN 60745-2-x (Uncertainty (k): noise 3 dB(A).

Cutting minerals

Basic tool data								Productivity data				
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material of productivity data	Metres till EAV 2.5 m/s ²	Metres till ELV 5 m/s ²	HSE Points
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1.5 m/s ²	120 min.	480 min.	DC-D 230-C1	cutting off 50 mm concrete slabs	61	244	1,64
								DC-D 230-C1	cutting grooves 30 mm deep in 40 N/mm ² concrete	54	216	1,85
								DC-D 230-C1	cutting grooves 45 mm deep in sand-limestone	71	284	1,41
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1.5 m/s ²	120 min.	480 min.	DC-D 230-C1	cutting off 50 mm concrete slabs	79	316	1,27
								DC-D 230-C1	cutting grooves 30 mm deep in 40 N/mm ² concrete	60	240	1,67
								DC-D 230-C1	cutting grooves 45 mm deep in sand-limestone	117	468	0,85
DCG 230-DB (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1.5 m/s ²	120 min.	480 min.	DC-D 230-C1	cutting off 50 mm concrete slabs	70	280	1,43
								DC-D 230-C1	cutting grooves 30 mm deep in 40 N/mm ² concrete	80	320	1,25
								DC-D 230-C1	cutting grooves 45 mm deep in sand-limestone	108	432	0,93

* Emission sound pressure level LpA and triaxial vibration value ahv according to EN 60745-2-x or EN62841-2-X (Uncertainty (k): noise 3 dB(A), vibration n.a).

Steel cutting tools

Cutting rebar

Basic tool data								Productivity data								
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²)							
									HSE Points							
									10	12	15	20	25			
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 2.5mm USP	1860 (7440)	1150 (4600)	610 (2440)	380 (1520)	0,05 0,09	0,16 0,26		
								AC-D 230 1.8mm Inox	1950 (7800)	1220 (4880)	660 (2640)	420 (1680)	0,05 0,08	0,15 0,24		
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	1140 (4560)	760 (3040)	480 (1920)	260 (1040)	170 (680)	0,09 0,13	0,21 0,38	0,59 0,99
								AC-D 125 2,5mm USP	450 (1800)	300 (1200)	190 (760)	100 (400)	70 (280)	0,22 0,33	1,00 1,43	
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox	3790 (15160)	2200 (8800)	1070 (4280)	640 (2560)	0,03 0,05	0,09 0,16		
								AC-D 230 2,5mm USP	3860 (15440)	2170 (8680)	1010 (4040)	580 (2320)	0,03 0,05	0,10 0,17		
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 1,5mm Inox	1490 (5960)	1060 (4240)	720 (2880)	430 (1720)	300 (1200)	0,07 0,09	0,14 0,23	0,33 0,59
								AC-D 125 2,5mm USP	620 (2480)	410 (1640)	260 (1040)	140 (560)	90 (360)	0,16 0,24	0,38 0,71	1,11 1,67
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox	3400 (13600)	2080 (8320)	1080 (4320)	680 (2720)	0,03 0,05	0,09 0,15		
								AC-D 230 2,5mm USP	1480 (5920)	1550 (6200)	840 (3360)	540 (2160)	0,07 0,06	0,12 0,19		
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1,5mm Inox	1340 (5360)	890 (3560)	560 (2240)	300 (1200)	200 (800)	0,07 0,11	0,18 0,33	0,50 0,99
								AC-D 125 2,5mm USP	430 (1720)	280 (1120)	170 (680)	90 (360)	60 (240)	0,23 0,36	0,59 1,11	1,67 2,59

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Steel cutting tools

Cutting rebar

Basic tool data								Productivity data	
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²) HSE Points Diameter 16mm
AG 115-D/-S (03)	n/a	92 dB(A)	103 dB(A)	6,5 m/s ²	1,5 m/s ²	71 min.	288 min.	AC-D SPX 115x1.0mm	940 (3760) 0,11
AG 125-13S (04)	DC-EX	92 dB(A)	103 dB(A)	4,9 m/s ²	1,5 m/s ²	125 min.	500 min.	AC-D SPX 125x1.0mm	1785 (7140) 0,06
AG 125-15DB (04)	DC-EX	91 dB(A)	102 dB(A)	4,4 m/s ²	1,5 m/s ²	155 min.	620 min.	AC-D SPX 125x1.0mm	2319 (9276) 0,04
AG 125-19SE (04)	DC-EX	87 dB(A)	98 dB(A)	4,9 m/s ²	1,5 m/s ²	125 min.	500 min.	AC-D SPX 125x1.0mm	2179 (8716) 0,05

								Diameter 26mm	
AG 180-20P (03)	n/a	97 dB(A)	108 dB(A)	6,2 m/s ²	1,5 m/s ²	78 min.	312 min.	AC-D SPX 180x1.5mm	311 (1244) 0,32
AG 230-24D (04)	DC-EX	94 dB(A)	105 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	357 min.	AC-D SPX230x1.8mm	395 (1580) 0,25
AG 230-27DB (04)	DC-EX	90 dB(A)	101 dB(A)	6,3 m/s ²	1,5 m/s ²	76 min.	302 min.	AC-D SPX230x1.8mm	346 (1384) 0,29

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

								Diameter 26mm	
AG 125-A22 (02)	DC-EX	83 dB(A)	94 dB(A)	3,8 m/s ²	1,5 m/s ²	208 min.	831 min.	AC-D SPX 125x1.0mm	656 (2624) 0,15
AG 125-A36 (01)	DC-EX	80 dB(A)	91 dB(A)	3,2 m/s ²	1,5 m/s ²	293 min.	1172 min.	AC-D SPX 125x1.0mm	1172 (4688) 0,09

Steel cutting tools
Cutting channel installation systems

Tool	Dust removal available	Basic tool data						Productivity data			
		Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts through channel to EAV 2.5 m/s2 (ELV 5 m/s2) HSE Points		
		MQ 21/2	MQ 41/2	MQ 41/3							
AG 125-A22 (01)	DC-EX	83 dB(A)	94 dB(A)	3,8 m/s ²	1,5 m/s ²	208 min.	832 min.	AC-D 125 Inox USP 1.0mm	1440 (5760) 0,07		
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 1.8 Inox	1210 (4840) 0,08	820 (3280) 0,12	550 (2200) 0,18
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	470 (1880) 0,21	320 (1280) 0,31	220 (880) 0,45
								AC-D 125 2,5mm USP	190 (760) 0,53	130 (520) 0,77	90 (360) 1,11
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox	2790 (11160) 0,04	1390 (5560) 0,07	870 (3480) 0,11
								AC-D 230 2,5mm USP	2150 (8600) 0,05	1330 (5320) 0,08	810 (3240) 0,12
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 1,5mm Inox	720 (2880) 0,14	520 (2080) 0,19	370 (1480) 0,27
								AC-D 125 2,5mm USP	260 (1040) 0,38	180 (720) 0,56	120 (480) 0,83
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox	2060 (8240) 0,05	1370 (5480) 0,07	900 (3600) 0,11
								AC-D 230 2,5mm USP	1540 (6160) 0,06	1040 (4160) 0,10	700 (2800) 0,14
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1,5mm Inox	560 (2240) 0,18	380 (1520) 0,26	250 (1000) 0,40
								AC-D 125 2,5mm USP	170 (680) 0,59	120 (480) 0,83	80 (320) 1,25

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Steel cutting tools
Cutting steel bars (square)

Tool	Dust removal available	Emission sound pressure level LpA*	Basic tool data				Time to EAV	Time to ELV	Cutting Wheel	Productivity data				
			Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Square steel								
						Number of cuts through dimensions [mm] to EAV 2.5 m/s2 (ELV 5 m/s2) HSE Points								
									13	20	25	30	40	
AG 125-A22 (01)	DC-EX	83 dB(A)	94 dB(A)	3,8 m/s ²	1,5 m/s ²	208 min.	832 min.	AC-D 125 Inox USP 1.0mm	1590					
									(6360)					
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 2.5mm USP	1200	470	290	190	100	
									(4800)	(1880)	(1160)	(760)	(400)	
								AC-D 230 1,8mm Inox	1400	540			110	
									(5600)	(2160)			(440)	
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	550	215				
								AC-D 125 2,5mm USP	220	80				
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	2570	790			110	
								AC-D 230 1,8mm Inox	2580	850			140	
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 2,5mm USP	300	120				
								AC-D 125 1,5mm Inox	810	370				
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	1780	680			140	
								AC-D 230 1,8mm Inox	2400	870			170	
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 2,5mm USP	200		70			
								AC-D 125 1,5mm Inox	640		250			

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Steel cutting tools
Cutting steel bars (flat)

Tool	Dust removal available	Emission sound pressure level LpA*	Basic tool data					Productivity data				
			Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Flat steel Number of cuts through dimensions [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²) HSE Points			
									10 x 50	20 x 60	30 x 60	30 x 80
AG 125-A22 (01)	DC-EX	83 dB(A)	94 dB(A)	3,8 m/s ²	1,5 m/s ²	208 min.	832 min.	AC-D 125 Inox USP 1.0mm	630			
									(2520)			
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 2.5mm USP	370	140	90	65
									(1480)	(560)	(360)	(260)
								AC-D 230 1,8mm Inox	420			70
									(1680)			(280)
DAG 115-S (02)	n/a	86 dB(A)	97 dB(A)	7,5 m/s ²	1,5 m/s ²	53 min.	212 min.	AC-D 115 1,0mm Inox USP	370	140		
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	(1480)	(560)		
									0,27	0,71		
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	90			
									(360)			
								AC-D 230 1,8mm Inox	170			
									(680)			
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	70	30		
									(280)	(120)		
								AC-D 230 1,8mm Inox	590			60
									(2360)			(240)
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	0,17			1,67
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	650			80
									(2600)			(320)
								AC-D 230 1,8mm Inox	0,15			1,25
									540			100
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	(2160)			(400)
									0,19			1,00
								AC-D 230 1,8mm Inox	680			90
									(2720)			(360)
									0,15			1,11

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Steel cutting tools - Cutting cable trays

Basic tool data								Productivity data							
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²)						
									HSE Points						
									50mm	100mm	150mm	225mm	300mm	600mm	
AG 125-A22 (01)	DC-EX	83 dB(A)	94 dB(A)	3,8 m/s ²	1,5 m/s ²	208 min.	832 min.	AC-D 125 Inox USP 1.0mm					980		
													(3920)		
													0,10		
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 1,8mm Inox USP	1590	1120	1340	820	740	350	
									(6360)	(4480)	(5360)	(3280)	(2960)	(1400)	
									0,06	0,09	0,07	0,12	0,14	0,29	
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	620	440	520	320	290	155	
									(2480)	(1760)	(2080)	(1280)	(1160)	(620)	
									0,16	0,23	0,19	0,31	0,34	0,65	
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 2,5mm USP	250	170	210	130	120	60	
									(1000)	(680)	(840)	(520)	(480)	(240)	
									0,40	0,59	0,48	0,77	0,83	1,67	
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox USP	3000	2000	2450	1380	1230	520	
									(12000)	(8000)	(9800)	(5520)	(4920)	(2080)	
									0,03	0,05	0,04	0,07	0,08	0,19	
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	3000	1950	2420	1320	1160	470	
									(12000)	(7800)	(9680)	(5280)	(4640)	(1880)	
									0,03	0,05	0,04	0,08	0,09	0,21	
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 1,5mm Inox USP	890	670	780	520	480	240	
									(3560)	(2680)	(3120)	(2080)	(1920)	(960)	
									0,11	0,15	0,13	0,19	0,21	0,42	
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 2,5mm USP	340	240	290	180	160	85	
									(1360)	(960)	(1160)	(720)	(640)	(340)	
									0,29	0,42	0,34	0,56	0,63	1,18	
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox USP	2740	1900	2290	1360	1220	560	
									(10960)	(7600)	(9160)	(5440)	(4880)	(2240)	
									0,04	0,05	0,04	0,07	0,08	0,18	
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	2020	1420	1700	1040	940	450	
									(8080)	(5680)	(6800)	(4160)	(3760)	(1800)	
									0,05	0,07	0,06	0,10	0,11	0,22	
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1,5mm Inox USP	730	510	610	370	340	185	
									(2920)	(2040)	(2440)	(1480)	(1360)	(740)	
									0,14	0,20	0,16	0,27	0,29	0,54	
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 2,5mm USP	230	160	190	120	100	55	
									(920)	(640)	(760)	(480)	(400)	(220)	
									0,43	0,63	0,53	0,83	1,00	1,82	

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Cutting sheet steel metal

Basic tool data								Productivity data						
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²)					
									HSE Points					
									steel sheet metal (400mm x 1,4mm)					
AG 125-A22 (01)	DC-EX	83 dB(A)	94 dB(A)	3,8 m/s ²	1,5 m/s ²	208 min.	832 min.	AC-D 125 Inox USP 1.0mm					580	
													(2320)	
													0,17	

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Circular sawing metal

Basic tool data								Productivity data				
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material		Metres till EAV 2.5 m/s ²	Metres till EAV 5 m/s ²
									HSE Points			
SCM 22-A (01)	n/a	77 dB(A)	88 dB(A)	1.2 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	all, Quick, Multi, Qualicut	Cutting off 3 mm sheet metal		2500	10000
											0,04	

* Emission sound pressure level LpA and triaxial vibration value ahv according to European Standard EN 60745-2-x or EN62841-2-X (Uncertainty (k): noise 3 dB(A)).

Steel cutting tools
Cutting round steel bars

Basic tool data								Productivity data						
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²)					
									HSE Points					
								10mm	12mm	15mm	20mm	30mm	40mm	
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 2,5mm USP	2770 (11080) 0,04	1860 (7440) 0,05		61 (244) 1,64	250 (1000) 0,40	130 (520) 0,77
								AC-D 230 1,8mm Inox USP		2180 (8720) 0,05	1320 (5280) 0,08			
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP		840 (3360) 0,12	520 (2080) 0,19			
								AC-D 125 2,5mm USP		330 (1320) 0,30	210 (840) 0,48			
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox USP		4320 (17280) 0,02	2410 (9640) 0,04			
								AC-D 230 2,5mm USP		4440 (17760) 0,02	2390 (9560) 0,04			
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 1,5mm Inox USP		1160 (4640) 0,09	770 (3080) 0,13			
								AC-D 125 2,5mm USP		460 (1840) 0,22	290 (1160) 0,34			
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox USP		3830 (15320) 0,03	2260 (9040) 0,04			
								AC-D 230 2,5mm USP		2770 (11080) 0,04	1680 (6720) 0,06			
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1,5mm Inox USP		990 (3960) 0,10	600 (2400) 0,17			
								AC-D 125 2,5mm USP		320 (1280) 0,31	190 (760) 0,53			

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Steel cutting tools
Cutting steel pipes

Basic tool data								Productivity data				
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts through diameter [mm] to EAV 2.5 m/s2 (ELV 5 m/s2)			
									HSE points			
									1" steel pipe diameter: 33.8 mm thickness: 2.8 mm	2" steel pipe diameter: 60.4 mm thickness: 2.8 mm	3" steel pipe diameter: 89 mm thickness: 2.8 mm	
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 2.5mm USP	710	360		
									(2840)	(1440)		
									0,14	0,28		
									880	390		
									(3520)	(1560)		
									0,11	0,26		
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	350	160		
									(1400)	(640)		
									0,29	0,63		
									140	60		
									(560)	(240)		
									0,71	1,67		
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2.5mm USP	1440	530	270	
									(5760)	(2120)	(1080)	
									0,07	0,19	0,37	
									1550	590	310	
									(6200)	(2360)	(1240)	
									0,06	0,17	0,32	
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 230 1.8mm Inox	550	280		
									(2200)	(1120)		
									0,18	0,36		
									190	90		
									(760)	(360)		
									0,53	1,11		
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1.8mm Inox	1470	630	350	
									(5880)	(2520)	(1400)	
									0,07	0,16	0,29	
									1120	500	290	
									(4480)	(2000)	(1160)	
									0,09	0,20	0,34	
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1.5mm Inox	400	180		
									(1600)	(720)		
									0,25	0,56		
									120	60		
									(480)	(240)		
									0,83	1,67		

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Steel cutting tools
Cutting rods - M10

Basic tool data								Productivity data		
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²)	
									HSE Points	
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 1,5mm Inox USP	1340	(5360)
								AC-D 125 2,5mm USP	1080	(4320)
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1,5mm Inox USP	2340	(9360)
								AC-D 125 2,5mm USP	760	(3040)
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	1980	(7920)
								AC-D 125 2,5mm USP	770	(3080)

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x. Uncertainty (k): noise 3dB

Cutting pipes

Basic tool data								Productivity data			
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²)		
									HSE Points		
									Pipe OD 42,4 x 2	Pipe OD 42,4 x 3.25	
DAG 115-S (02)	n/a	86 dB(A)	97 dB(A)	7,5 m/s ²	1,5 m/s ²	53 min.	212 min.	AC-D 115 2,5mm USP	200	110	
									(800)	(440)	
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	350	210	
									(1400)	(840)	
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	1450	780	
									(5800)	(3120)	
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 1.8mm Inox USP	880	530	
									(3520)	(2120)	
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 1,5mm Inox USP	550	360	
								AC-D 125 2,5mm USP	190	110	
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 2,5mm USP	1120	670	
								AC-D 230 2,5mm USP	(4480)	(2680)	
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1,5mm Inox USP	400	250	
								AC-D 125 2,5mm USP	(520)	(280)	

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Steel cutting tools
Cutting pipes

Basic tool data								Productivity data		
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²) HSE Points	
									13mm steel pipe (Ø 13.1 x 1.2mm)	22 mm steel pipe (Ø22.2 x 1.2mm)
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	2320	1250
									(9280)	5000
								AC-D 125 2,5mm USP	900	490
									(3600)	(1960)
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 1,5mm Inox USP	2700	1610
									(10800)	(6440)
								AC-D 125 2,5mm USP	1270	690
									(5080)	(2760)
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1,5mm Inox USP	2740	1480
									(10960)	(5920)
								AC-D 125 2,5mm USP	900	470
									(3600)	(1880)

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x. Uncertainty (k): noise 3dB

Cutting C-Rails

Basic tool data								Productivity data		
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²) HSE Points	
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 1,8mm Inox USP	1060	
									(4240)	0,09
DAG 115-S (02)	n/a	86 dB(A)	97 dB(A)	7,5 m/s ²	1,5 m/s ²	53 min.	212 min.	AC-D 115 2,5mm USP	250	
									(1000)	0,40
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 1 25 1,5mm Inox USP	420	
									(1680)	0,24
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox USP	1880	
									(7520)	0,05
								AC-D 230 2,5mm USP	1830	
									(7320)	0,05
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 1,5mm Inox USP	640	
									(2560)	0,16
								AC-D 125 2,5mm USP	230	
									(920)	0,43
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox USP	1800	
									(7200)	0,06
								AC-D 230 2,5mm USP	1350	
									(5400)	0,07
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1,5mm Inox USP	490	
									(1960)	0,20
								AC-D 125 2,5mm USP	150	
									(600)	0,67

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Steel cutting tools
Cutting ducts

Basic tool data								Productivity data				
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²)			
									HSE Points			
								100 mm Ø duct x 0.5mm w.t	200 mm Ø duct x 0.6mm w.t.	355 mm Ø duct x 0.8mm w.t.		
AG 125-A22 (01)	yes	83 dB(A)	94 dB(A)	3,8 m/s ²	1,5 m/s ²	208 min.	832 min.	AC-D 125 Inox USP 1.0mm	1190			
									(4760)			
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	1230	280	100	
									(4920)	(1120)	(400)	
								AC-D 125 2,5mm USP	480	110	35	
									(1920)	(440)	(140)	
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox USP	6750	1150	255	
									(27000)	(4600)	(1020)	
								AC-D 230 2,5mm USP	7100	1100	220	
									(28400)	(4400)	(880)	
DC 230-S (01)	n/a	92 dB(A)	103 dB(A)	5,8 m/s ²	1,5 m/s ²	89 min.	356 min.	AC-D 230 1,8mm Inox USP	3200	700	190	
									(12800)	(2800)	(760)	
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 2,5mm USP	670	150	45	
									(2680)	(600)	(180)	
								AC-D 125 1,5mm Inox USP	1590	460	140	
									(6360)	(1840)	(560)	
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox USP	5750	1150	295	
									(23000)	(4600)	(1180)	
								AC-D 230 2,5mm USP	4050	900	240	
									(16200)	(3600)	(960)	
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 2,5mm USP	450	100	30	
									(1800)	(400)	(120)	
								AC-D 125 1,5mm Inox USP	1450	325	100	
									(5800)	(1300)	(400)	
								0,07	0,31	1,00		

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Cutting pipes

Basic tool data								Productivity data			
Tool	Dust removal available	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²)		
									HSE Points		
								steel pipe 17.2x1.8mm EN 10216-1	steel pipe 21.3x2.0mm EN 10216-1	steel pipe 33.7x2.6mm EN 10216-1	
AG 125-A22 (01)	yes	83 dB(A)	94 dB(A)	3,8 m/s ²	1,5 m/s ²	208 min.	832 min.	AC-D 125 Inox USP 1.0mm	2800	2100	1130
									(11200)	(8400)	(4520)
								0,04	0,05	0,09	

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Steel cutting tools - Cutting sheet metal decking *Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Basic tool data								Productivity data		
Tool	Dust removal available	Emission sound pressure Level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty K	Time to EAV	Time to ELV	Cutting Wheel	Work piece material of productivity data	Number of cuts for diameter [mm] to EAV 2.5 m/s ² (ELV 5 m/s ²) HSE points
DAG 115-S (02)	n/a	86 dB(A)	97dB(A)	7,5 m/s ²	1,5 m/s ²	53 min.	212 min.	AC-D 115 2,5mm USP	Structural metal decking 1.2mm thick cut along deck 1m	45 (180) 2,22
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	35 (140) 2,86
DAG 125-S (01)	n/a	87 dB(A)	98 dB(A)	4,6 m/s ²	1,5 m/s ²	142 min.	568 min.	AC-D 125 1,5mm Inox USP	Structural metal decking 1.2mm thick cut along deck 1m	75 (300) 1,33
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	55 (220) 1,82
DAG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox	Structural metal decking 1.2mm thick cut along deck 1m	340 (1360) 0,29
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	260 (1040) 0,38
								AC-D 230 2,5mm USP	Structural metal decking 1.2mm thick cut along deck 1m	330 (1320) 0,30
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	255 (1020) 0,39
DCG 125-S (01)	n/a	90 dB(A)	101 dB(A)	5,7 m/s ²	1,5 m/s ²	92 min.	368 min.	AC-D 125 1,5mm Inox USP	Structural metal decking 1.2mm thick cut along deck 1m	115 (460) 0,87
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	85 (340) 1,18
								AC-D 125 2,5mm USP	Structural metal decking 1.2mm thick cut along deck 1m	40 (160) 2,50
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	30 (120) 3,33
DCG 230-D (01)	n/a	90 dB(A)	101 dB(A)	5,0 m/s ²	1,5 m/s ²	120 min.	480 min.	AC-D 230 1,8mm Inox USP	Structural metal decking 1.2mm thick cut along deck 1m	325 (1300) 0,31
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	250 (1000) 0,40
								AC-D 230 2,5mm USP	Structural metal decking 1.2mm thick cut along deck 1m	240 (960) 0,42
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	190 (760) 0,53
DEG 125-D (01)	n/a	89 dB(A)	100 dB(A)	7 m/s ²	1,5 m/s ²	61 min.	244 min.	AC-D 125 1,5mm Inox USP	Structural metal decking 1.2mm thick cut along deck 1m	85 (340) 1,18
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	65 (260) 1,54
								AC-D 125 2,5mm USP	Structural metal decking 1.2mm thick cut along deck 1m	25 (100) 4,00
									Structural metal decking 1.2mm thick cut across 60mm width,"Comflor 51"&"Metfloor 51"	20 (80) 5,00

Direct fastening tools

Cartridge tool	Cartridge color	Vibration		HSE Points	Noise Workplace relevant emission value $L_{pA,1s}$
		Recommended number of fastenings per day			
		EAV 2.5 m/s ²	ELV 5 m/s ²		
DX 351	white	2100	8400	0,05	101 dB(A)
	green	1900	7600	0,05	
	yellow	1100	4400	0,09	
	red	800	3200	0,13	
DX 460	green	1300	5200	0,08	101 dB(A)
	yellow	1000	4000	0,10	
	red	800	3200	0,13	
	black	600	2400	0,17	
DX 76	blue	700	2800	0,14	110 dB(A)
	red	600	2400	0,17	
	black	400	1600	0,25	

* Sound pressure level $L_{pA,1s}$ measured at user's ear according to standard EN 12549. Wear ear plugs according to operating instructions.

Cartridge tool	Cartridge color	Vibration		HSE Points	Noise Workplace relevant emission value $L_{pA,1s}$
		Recommended number of fastenings per day			
		EAV 2.5 m/s ²	ELV 5 m/s ²		
DX 9	blue	9600 (recommended)	38400 (recommended)	0,01	
	red	9600 (recommended)	38400 (recommended)	0,01	
	black	9600 (recommended)	38400 (recommended)	0,01	
DX 860 ENP	blue	3500	1400	0,03	106 dB(A)
	red	2600	10400	0,04	
	black	1800	7200	0,06	
DX 860 HSN	yellow	5600	22400	0,02	100 dB(A)
	red	5500	22000	0,02	
	black	3000	12000	0,03	
DX E72	brown	1000	4000	0,10	109 dB(A)
	green	900	3600	0,11	
	yellow	700	2800	0,14	
DX 2	green	600	2400	0,17	104 dB(A)
	yellow	500	2000	0,20	
	red	500	2000	0,20	
DX 5 (01)	green	1300	5100	0,08	101 dB(A)
	yellow	1000	4100	0,10	
	red	800	3300	0,13	
	black	600	2400	0,17	
DX 36	green	600	2400	0,17	100 dB(A)
	yellow	500	2000	0,20	
	red	500	2000	0,20	

* Sound pressure level $L_{pA,1s}$ measured at user's ear according to standard EN 12549. Wear ear plugs according to operating instructions.

Cartridge tool	Cartridge color	Vibration		HSE Points	Noise Workplace relevant emission value $L_{pA,1s}$
		Recommended number of fastenings per day			
		EAV 2.5 m/s ²	ELV 5 m/s ²		
DX A41	green	1300	5200	0,08	103 dB(A)
	yellow	1000	4000	0,10	
	red	1000	4000	0,10	
	black	600	2400	0,17	
DX 750	blue	600	2400	0,17	110 dB(A)
	red	500	2000	0,20	
	black	400	1600	0,25	

* Sound pressure level $L_{pA,1s}$ measured at user's ear according to standard EN 12549. Wear ear plugs according to operating instructions.

Direct fastening tools

Battery nail tool	Base material	Vibration		HSE Points	Noise Workplace relevant emission value $L_{pA^*,1s}$
		Recommended number of fastenings per day			
		EAV 2.5 m/s ²	ELV 5 m/s ²		
BX 3-ME (01)	concrete	11342	45369	0,01	89 dB(A)
BX 3-ME (02)	concrete	28800	115200	0,003	89 dB(A)
BX 3/3-L (02)	concrete	37440	149760	0,003	90 dB(A)
BX 3-BT (02)	concrete	37440	149760	0,003	94 dB(A)

* Sound pressure level $L_{pA^*,1s}$ measured at user's ear according to standard EN 12549. Wear ear plugs according to operating instructions.

Gas actuated nail tool	Base material	Vibration		HSE Points	Noise Workplace relevant emission value $L_{pA^*,1s}$
		Recommended number of fastenings per day			
		EAV 2.5 m/s ²	ELV 5 m/s ²		
GX 3/3-ME	concrete	27720	110880	0,004	99dB(A)
GX 120/GX 120-ME	concrete	22560	90240	0,004	102 dB(A)
GX 100/GX 100-E	concrete	2700	10800	0,04	102 dB(A)
GX 90 WF	wood	25000	100000	0,00	106 dB(A)

* Sound pressure level $L_{pA^*,1s}$ measured at user's ear according to standard EN 12549. Wear ear plugs according to operating instructions.

Saws

Reciprocating saws cutting steel pipes

Basic tool data								Productivity data				
Tool	Dust removal system	Emission sound pressure level LpA* ¹	Emission sound power level* ¹	Triaxial vibration value ahv* ²	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material of productivity data	Work till EAV 2.5 m/s ²	Work till ELV 5 m/s ²	HSE Points per cut
WSR 22-A (01)	n/a	>82 dB(A)	>89 dB(A)	n/a	n/a	n/a	n/a	W-CSR MS 15 P	cutting 17.2x1.8mm steelpipe	82 cuts	328 cuts	1,22
								W-CSR MS 15 P	cutting 21.3x2.0mm steelpipe	55 cuts	220 cuts	1,82
								W-CSR MS 15 P	cutting 33.7x2.6mm steelpipe	26 cuts	104 cuts	3,85
								W-CSR MS 15 P	cutting 60.3x2.9mm steelpipe	12 cuts	48 cuts	8,33
WSR 36-A (01)	no	>90 dB(A)	>101 dB(A)	n/a	n/a	n/a	n/a	W-CSR MQ 15	cutting 17.2x1.8mm steelpipe	170 cuts	680 cuts	0,59
								W-CSR MQ 15	cutting 21.3x2.0mm steelpipe	140 cuts	560 cuts	0,71
								W-CSR MQ 15	cutting 33.7x2.6mm steelpipe	45 cuts	180 cuts	2,22
								W-CSR MQ 15	cutting 60.3x2.9mm steelpipe	14 cuts	56 cuts	7,14
WSR 900-PE (01)	no	>89 dB(A)	>100 dB(A)	n/a	n/a	n/a	n/a	W-CSR MS 15 P	cutting 17.2x1.8mm steelpipe	175 cuts	700 cuts	0,57
								W-CSR MS 15 P	cutting 21.3x2.0mm steelpipe	135 cuts	540 cuts	0,74
								W-CSR MS 15 P	cutting 33.7x2.6mm steelpipe	47 cuts	188 cuts	2,13
								W-CSR MS 15 P	cutting 60.3x2.9mm steelpipe	19 cuts	76 cuts	5,26
								W-CSR MS 23 P	cutting 80.9x3.2mm steelpipe	9 cuts	36 cuts	11,11
WSR 1250-PE (01)	no	>89 dB(A)	>100 dB(A)	n/a	n/a	n/a	n/a	W-CSR MS 15 P	cutting 17.2x1.8mm steelpipe	84 cuts	336 cuts	1,19
								W-CSR MS 15 P	cutting 21.3x2.0mm steelpipe	48 cuts	192 cuts	2,08
								W-CSR MS 15 P	cutting 33.7x2.6mm steelpipe	19 cuts	76 cuts	5,26
								W-CSR MS 15 P	cutting 60.3x2.9mm steelpipe	14 cuts	56 cuts	7,14
								W-CSR MS 23 P	cutting 80.9x3.2mm steelpipe	7 cuts	28 cuts	14,29
WSR 1400-PE (01)	no	>89 dB(A)	>100 dB(A)	n/a	n/a	n/a	n/a	W-CSR MS 15 P	cutting 17.2x1.8mm steelpipe	188 cuts	752 cuts	0,53
								W-CSR MS 15 P	cutting 21.3x2.0mm steelpipe	127 cuts	508 cuts	0,79
								W-CSR MS 15 P	cutting 33.7x2.6mm steelpipe	44 cuts	176 cuts	2,27
								W-CSR MS 15 P	cutting 60.3x2.9mm steelpipe	21 cuts	84 cuts	4,76
								W-CSR MS 23 P	cutting 80.9x3.2mm steelpipe	10 cuts	40 cuts	10,00

¹ Emission sound pressure level and Emission sound power level values recorded here are for wood applications, so steel application values may differ depending on the work piece used

² Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Reciprocating saws cutting channels

Basic tool data								Productivity data				
Tool	Dust removal system	Emission sound pressure level LpA* ¹	Emission sound power level* ¹	Triaxial vibration value ahv* ²	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material of productivity data	Work till EAV 2.5 m/s ²	Work till ELV 5 m/s ²	HSE Points per cut
WSR 22-A (01)	n/a	>82 dB(A)	>93 dB(A)	n/a	n/a	n/a	n/a	W-CSR MQ 15	MQ 21/2 channel	28 cuts	112 cuts	3,57
								W-CSR MQ 15	MQ 41/3 channel	17 cuts	68 cuts	5,88
WSR 36-A (01)	n/a	>90 dB(A)	>101 dB(A)	n/a	n/a	n/a	n/a	W-CSR MQ 15	MQ 21/2 channel	55 cuts	220 cuts	1,82
								W-CSR MQ 15	MQ 41/3 channel	25 cuts	100 cuts	4,00
WSR 900-PE (01)	n/a	>89 dB(A)	>100 dB(A)	n/a	n/a	n/a	n/a	W-CSR MQ 15	MQ 21/2 channel	130 cuts	520 cuts	0,77
								W-CSR MQ 15	MQ 41/3 channel	47 cuts	188 cuts	2,13
WSR 1250-PE (01)	n/a	>89 dB(A)	>100 dB(A)	n/a	n/a	n/a	n/a	W-CSR MQ 15	MQ 21/2 channel	52 cuts	208 cuts	1,92
								W-CSR MQ 15	MQ 41/3 channel	25 cuts	100 cuts	4,00
WSR 1400-PE (01)	n/a	>89 dB(A)	>100 dB(A)	n/a	n/a	n/a	n/a	W-CSR MQ 15	MQ 21/2 channel	116 cuts	464 cuts	0,86
								W-CSR MQ 15	MQ 41/3 channel	45 cuts	180 cuts	2,22

¹ Emission sound pressure level and Emission sound power level values recorded here are for wood applications, so steel application values may differ depending on the work piece used

² Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

How to read the Tool Selector
Cutting

The length of material and number of cuts that can be made for a particular tool and application in one working day before reaching the EAV and ELV are listed under the productivity data.

Saws - Reciprocating saws

Basic tool data								Productivity data				
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material of productivity data	Work till EAV 2.5 m/s ²	Work till ELV 5 m/s ²	HSE Points per m or cut
WSR 22-A (01)	n/a	82 dB(A)	93 dB(A)	16 m/s ²	1.5 m/s ²	12 min.	48 min.	WU 20	Cutting off 38 mm chipboard	45 cuts	180 cuts	2,22
				18 m/s ²	1.5 m/s ²	9 min.	36 min.	WF 23	Cutting off (100 x 100) mm wooden beam	66 cuts	264 cuts	1,52
WSR 36-A (01)	no	90 dB(A)	101 dB(A)	13 m/s ²	5 m/s ²	18 min.	72 min.	WU 20	Cutting chipboard (thickness 38 mm)	100 cuts	402 cuts	1,00
				16 m/s ²	4 m/s ²	12 min.	48 min.	WF 23	Cutting wooden beams (100 x 100 mm fir)	86 cuts	344 cuts	1,16
WSR 650-A (01)	no	84 dB(A)	95 dB(A)	12 m/s ²	2.5 m/s ²	21 min.	84 min.	WU 20	Cutting chipboard (thickness 38 mm)	61 m	244 m	1,64
				16 m/s ²	5 m/s ²	12 min.	48 min.	WF 23	Cutting wooden beams (100 x 100 mm fir)	10 cuts	40 cuts	10,00
WSR 900-PE (01)	no	89 dB(A)	100 dB(A)	16 m/s ²	2.5 m/s ²	12 min.	48 min.	WU 20	Cutting chipboard (thickness 38 mm)	48 m	192 m	2,08
				23 m/s ²	3.5 m/s ²	6 min.	24 min.	WF 23	Cutting wooden beams (100 x 100 mm fir)	4 cuts	16 cuts	25,00
WSR 1250-PE (01)	no	90 dB(A)	101 dB(A)	22 m/s ²	2.5 m/s ²	6 min.	24 min.	WU 20	Cutting chipboard (thickness 38 mm)	28 m	112 m	3,57
				26.5 m/s ²	3.5 m/s ³	4 min.	16 min.	WF 23	Cutting wooden beams (100 x 100 mm fir)	4 cuts	16 cuts	25,00
WSR 1400-PE (01)	no	91 dB(A)	102 dB(A)	20 m/s ²	2.5 m/s ²	8 min.	32 min.	WU 20	Cutting chipboard (thickness 38 mm)	35 m	140 m	2,86
				28 m/s ²	3.5 m/s ³	4 min.	16 min.	WF 23	Cutting wooden beams (100 x 100 mm fir)	4 cuts	16 cuts	25,00
SR 2-A12 (01)	no	90 dB(A)	101 dB(A)	5.3 m/s ²	1.5 m/s ²	107 min.	428 min.					
SR 4-A12 (01)	no	84 dB(A)	95 dB(A)	5.5 m/s ²	1.5 m/s ²	99 min.	396 min.					
				16 m/s ²	2.5 m/s ²	12 min.	48 min.					
SR 4-A22 (01)	no	86 dB(A)	97 dB(A)	18 m/s ²	3.5 m/s ²	9 min.	37 min.	WU 20	Cutting chipboard (thickness 38 mm)	45 cuts	180 cuts	2,22
				18 m/s ²	3.5 m/s ²	9 min.	37 min.	WF 23	Cutting wooden beams (100 x 100 mm fir)	66 cuts	264 cuts	1,52
SR 6-A22 (01)	no	86 dB(A)	97 dB(A)	17.5	2.5 m/s ²	10 min.	39 min.	WU 20	Cutting chipboard (thickness 38 mm)	59 cuts	236 cuts	1,69
				21.3	3.5 m/s ³	7 min.	26 min.	WF 23	Cutting wooden beams (100 x 100 mm fir)	72 cuts	289 cuts	1,39
SR 30-A36 (01)	no	85 dB(A)	96 dB(A)	22.5	2.5 m/s ²	6 min.	24 min.	WU 20	Cutting chipboard (thickness 38 mm)	45 cuts	180 cuts	2,22
				20.5	3.5 m/s ³	7 min.	29 min.	WF 23	Cutting wooden beams (100 x 100 mm fir)	79 cuts	316 cuts	1,27

* Emission sound pressure level LpA and triaxial vibration value ahv according to EN 60745-2-x or EN62841-2-X (Uncertainty (k): noise 3 dB(A), depending on tool and application).

Jig saws

Basic tool data								Productivity data				
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material of productivity data	Work till EAV 2.5 m/s ²	Work till ELV 5 m/s ²	HSE Points per m or cut
WSJ 750-EB (01)	WSJ-DRS	88 dB(A)	99 dB(A)	13 m/s ²	1.5 m/s ²	18 min.	72 min.	W91/P HCS	Cutting chipboard (thickness 38 mm)	50 m	200 m	2,00
				5 m/s ²	1.5 m/s ²	120 min.	480 min.	M50/2 BIM	Cutting off 3mm sheet metal	23 m	92 m	4,35
WSJ 750-ET (01)	WSJ-DRS	87 dB(A)	98 dB(A)	10.5 m/s ²	1.5 m/s ²	27 min.	108 min.	W91/P HCS	Cutting chipboard (thickness 38 mm)	70 m	280 m	1,43
				4 m/s ²	1.5 m/s ²	188 min.	752 min.	M50/2 BIM	Cutting off 3mm sheet metal	26 m	104 m	3,85
WSJ 850-EB (01)	WSJ-DRS	88 dB(A)	99 dB(A)	11 m/s ²	1.5 m/s ²	25 min.	100 min.	W91/P HCS	Cutting chipboard (thickness 38 mm)	75 m	300 m	1,33
				5 m/s ²	1.5 m/s ²	120 min.	480 min.	M50/2 BIM	Cutting off 3mm sheet metal	24 m	96 m	4,17
WSJ 850-ET (01)	WSJ-DRS	87 dB(A)	98 dB(A)	9 m/s ²	1.8 m/s ²	37 min.	148 min.	W91/P HCS	Cutting chipboard (thickness 38 mm)	110 m	440 m	0,91
				4 m/s ²	1.5 m/s ²	188 min.	752 min.	M50/2 BIM	Cutting off 3mm sheet metal	29 m	116 m	3,45
SJD 6-A22 (01)	no	87 dB(A)	98 dB(A)	5.8 m/s ²	1.5 m/s ²	89 min.	357 min.	HILTI Quick cut W91/P	Cutting off 24mm OSB	261 m	1044 m	0,38
SJT 6-A22 (01)	no	89 dB(A)	98 dB(A)	5 m/s ²	1.5 m/s ²	120 min.	480 min.	HILTI Quick cut W91/P	Cutting off 24mm OSB	331 m	1324 m	0,3

* Emission sound pressure level LpA and triaxial vibration value ahv according to EN 60745-2-x or EN62841-2-X (Uncertainty (k): noise 3 dB(A), depending on tool and application).

Saws
Circular saws

Basic tool data								Productivity data				
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material of productivity data	Metres till EAV 2.5 m/s ²	Metres till ELV 5 m/s ²	HSE Points per m or cut
SCW 22-A (01)	VC	93 dB(A)	104 dB(A)	1.2 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	all, Quick, Multi, Qualicut	Cutting off 38 mm chipboard	13500 m	54000 m	0,01
								all, Quick, Multi, Qualicut	Cutting 55 mm softwood	1800 m	7200 m	0,06
SC 70W-A22 (01)	VC	81 dB(A)	92 dB(A)	1.3 m/s ²	1.5 m/s ²	>1440 min.	>1440 min.	Hilti Universal 190x1.8/1.1x30				
SC 55 W (01)	VC	89 dB(A)	100 dB(A)	2.2 m/s ²	1.5 m/s ²	620 min.	>1440 min.	Hilti Universal 190x1.8/1.1x30				
WSC 55-A24 (01)	VC	95 dB(A)	106 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	all, Quick, Multi, Qualicut	Cutting off 38 mm chipboard	5200 m	20800 m	0,02
								all, Quick, Multi, Qualicut	Cutting 55 mm softwood	3000 m	12000 m	0,03
WSC-55 (02)	VC	94 dB(A)	105 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	all, Quick, Multi, Qualicut	Cutting off 38 mm chipboard	9000 m	36000 m	0,01
								all, Quick, Multi, Qualicut	Cutting 55 mm softwood	4000 m	16000 m	0,03
WSC 70-A36 (01)	VC	97 dB(A)	108 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	all, Quick, Multi, Qualicut	Cutting off 38 mm chipboard	7400 m	29600 m	0,01
								all, Quick, Multi, Qualicut	Cutting 55 mm softwood	4800 m	19200 m	0,02
WSC 70 (01)	VC	94 dB(A)	105 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	all, Quick, Multi, Qualicut	Cutting off 38 mm chipboard	5000 m	20000 m	0,02
								all, Quick, Multi, Qualicut	Cutting 70 mm softwood	4000 m	16000 m	0,03
WSC 85 (01)	VC	100 dB(A)	111 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	all, Quick, Multi, Qualicut	Cutting off 38 mm chipboard	3300 m	13200 m	0,03
								all, Quick, Multi, Qualicut	Cutting 80 mm softwood	1200 m	4800 m	0,08
WSC 255 (01)	VC	92 dB(A)	103 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	all, Quick, Multi, Qualicut	Cutting off 38 mm chipboard	3500 m	14000 m	0,03
								all, Quick, Multi, Qualicut	Cutting 55 mm softwood	3300 m	13200 m	0,03
WSC-265-KE (01)	VC	89 dB(A)	100 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	>1440 min.	all, Quick, Multi, Qualicut	Cutting off 38 mm chipboard	2500 m	10000 m	0,04
								all, Quick, Multi, Qualicut	Cutting 65 mm softwood	3000 m	12000 m	0,03

* Emission sound pressure level and Emission sound power level values recorded here are for wood applications, so steel application values may differ depending on the work piece used
 * Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Cordless band saw

Basic tool data								Productivity data				
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material of productivity data	Work till EAV 2.5 m/s ²	Work till ELV 5 m/s ²	HSE Points per cut
SB 4-A22	no	73 dB(A)	84 dB(A)	<2,5 m/s ²	1.5 m/s ²	>480 min.	>1440 min.	SP 28 14/18	cutting off 2" steel pipe	2400 cuts	9600 cuts	0,04

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

Cordless cut-out tools

Basic tool data								Productivity data				
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Saw blade	Application & Work piece material of productivity data	Work till EAV 2.5 m/s ²	Work till ELV 5 m/s ²	HSE Points per cut
SCO 6-A22	no	73 dB(A)	84 dB(A)	<2,5 m/s ²	1.5 m/s ²	>480 min.	>1440 min.	SCOB D (1/8" standard bit)	cutting in 5/8" drywall	1930 m	7720 m	0,05

* Emission sound pressure level LpA and triaxial vibration value ahv according to the relevant European Standard EN 60745-2-x or EN62841-2-X. Uncertainty (k): noise 3dB

How to read the Tool Selector
Cutting

The length of material and number of cuts that can be made for a particular tool and application in one working day before reaching the EAV and ELV are listed under the productivity data.

Hydraulic tools
Pipe pressing / cutting / crimping tools

Basic tool data											
Tool	Dust removal system	Emission sound pressure level LpA*	Emission sound power level*	Triaxial vibration value ahv*	Uncertainty k	Time to EAV	Time to ELV	Application & Work piece material of productivity data	Operations till EAV 2.5 m/s ²	Operations till ELV 5 m/s ²	HSE Points per m or cut
NPR 19-A (01)	no	70 dB(A)	80 dB(A)	>2,5 m/s ²	1.5 m/s ²	>480 min.	>1440 min.	pressing operation	7200	28800	0,01
NPR 32-A (01)	no	81 dB(A)	92 dB(A)	2,5 m/s ²	1.5 m/s ²	480 min.	1440 min.	pressing operation	4114	16456	0,02
NUN 54-A (01)	no	89 dB(A)	100 dB(A)	>2,5 m/s ²	1.5 m/s ²	>480 min.	>1440 min.	crimping	6981	27924	0,01
NCT 25-A (01)	no	95 dB(A)	106 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	1440 min.	cutting cables	4800	19200	0,02
NCR 120-A (01)	no	89 dB(A)	100 dB(A)	2,5 m/s ²	1.5 m/s ²	480 min.	1440 min.	crimping			
NCT 85-A (01)	no	70 dB(A)	80 dB(A)	2.5 m/s ²	1.5 m/s ²	480 min.	1440 min.	cutting cables			

Disclaimer

Disclaimer for power tool selector

The vibration emission levels given in this information sheet have been measured in accordance with a standardised test described in EN 60745-1: 2006 or EN 61029 and may be used to compare one tool with another. They may be used for a preliminary assessment of exposure.

The declared vibration emission levels represent the main applications of the tools. However if the tools are used for different applications, with different accessories or are poorly maintained, the vibration emission may differ. This may significantly increase the exposure level over the total working period.

An estimation of the level of exposure to vibration should also take into account the times when the tool is switched off or when it is running but not actually doing the job. This may significantly reduce the exposure level over the total working period.

The respective numbers shown in the selector indicate as follows:

– Rotary hammers (1):

Numbers of holes that can be drilled in one working day without exceeding the exposure action value or exposure limit value as defined in the EU vibration directive 2002/44/EC.

– Combi hammers (2):

Numbers of holes that can be drilled or respectively the size of opening that can be chiselled in one working day without exceeding the exposure action value or exposure limit value as defined in the EU vibration directive 2002/44/EC.

– Breakers (3):

The size of opening that can be chiselled in one working day without exceeding the exposure action value or exposure limit value as defined in the EU vibration directive 2002/44/EC.

– Diamond coring tools (4):

Numbers of hole that can be drilled in one working day without exceeding the exposure action value or exposure limit value as defined in the EU vibration directive 2002/44/EC.

– Reciprocating saws (5):

Number of cutting meters that can be cut or respectively the number of cuts that can be performed in one working day without exceeding the exposure action value or exposure limit value as defined in the EU vibration directive 2002/44/EC.

The vibration values listed are triaxial measurements made in accordance with EN 60745-1:2006 or EN 61029.

The vibration values shown are generated from laboratory test data and do not guarantee actual vibration values for any specific application on site. The values are rounded averages.

Noise values are measured in accordance with EN 60745-1:2006 or EN 61029.

Regardless of the noise value, Hilti strongly recommends that appropriate noise protection is worn.

The material used for the measurements is defined as following:

– Rotary hammers, combi hammers, breakers and diamond coring tools are measured on concrete with a minimum compressive strength of 40 N/mm² (after 28 days). The concrete is not reinforced. The depth of the holes drilled is stated in the respective table.
– Reciprocating saws are measured on chipboard with the dimensions of 600 x 38 mm and beams of fir wood with the dimensions of 100 x 100 mm.

The size of opening chiselled by the small breakers up to and including the TE 706 represents chiselling out an opening in a wall (e.g. for a window) in solid material, i.e. the opening is surrounded by concrete on all sides.

When chiselling at the edge of a slab, performance is higher by a factor of 2–3. With the TE 805 and TE 905-AVR, the application is demolition chiselling towards the ground on an edge.

Disclaimer for direct fastening selector

The vibration and noise values listed in this table are generated from laboratory tests and do not guarantee actual recoil values in any specific application on site. The values are rounded averages.

These vibration and noise values are therefore to be used as a guideline only. The employer is responsible for adhering to local requirements applicable to workplace health and safety and for evaluation of the actual vibration and noise values by taking the appropriate on-site measurements.

Underlying measurements for vibration values are one-dimensional and taken in typical applications under laboratory conditions in accordance with ISO 8662-11.

Underlying measurements for noise values are taken in typical applications under laboratory conditions in accordance with EN 12 549 acoustics – noise test code for fastener driving tools.

The productivity values are calculated on the basis of the vibration value and performance of the tool and are measured in the procedures according to EN 60745-1:2006 or EN 61029. They vary, depending on many factors, such as the material, possible rebar hits, type and sharpness of the bit, chisel or blade used and the working behaviour of the user etc. All values are measured using new Hilti power tools and bits, chisels, blades etc.

Drilling into or through rebars influences the rate of drilling progress and vibration emissions. This, as a rule, leads to a significant reduction of overall productivity (decrease in the number of holes drilled).

The values given in the tool and application selectors are therefore to be used only as a guideline. The employer is responsible for ensuring that limit values are not exceeded.

The efficiency of dust removal systems depends strongly on their correct use as well as the conditions on the jobsite, e.g. the type and surface shape of the material worked on. The values given and statements made with respect to dust removal are therefore an indication only.

Dust from material such as paint containing lead, some wood species, minerals and metal may be harmful.

Certain kinds of dust are classified as carcinogenic such as oak and beech dust especially in conjunction with additives for wood conditioning (chromate, wood preservative). Material containing asbestos must only be treated by specialists.

- Where the use of a dust extraction device is possible it shall be used.
- The work place must be well ventilated.
- The use of a dust mask of filter class P2 is recommended.

Follow local requirements for the materials you want to work with.